WTF®
WORLD'S TOUGHEST FIX

CE

# DECLARATION OF PERFORMANCE - DOP

#DOP23039/0757



| Product name |
| --- |
| ***WTF I Invisible Flex*** |

1. **Type of product**
   1 component MS hybrid polymer

2. **Application**
   Sealant for the application in facades and in sanitary and wet areas sealing
   Type F, INT
   Conditioning: Method B

3. **Manufacturer / Importer**
   Rakennuskemia Oy, Kerkkolankatu 17, FIN-05800 Hyvinkää, Suomi

4. **System of assessment of constancy of performance**
   3 plus 3

5. **Harmonised Standard**
   EN 15651-1: 2012-12

6. **Notified body**
   NB 0757, as notified laboratory in system 3, performed the initial test and issued the test report.

WTF®
WORLD'S TOUGHEST FIX

CE

# DECLARATION OF PERFORMANCE - DOP

#DOP23039/0757



**7. Essential characteristics**

| **Essential characteristics** | **Performance** | Harmonised technical specification |
|---|---|---|
| Reaction to fire | Class E | EN 15651-1: 2012-12 |
| Release of chemicals dangerous to the environment and health | Evaluated | |
| Water tightness and air tightness | | |
| a) Resistance to flow | ≤ 5mm | |
| b) Loss of volume | ≤ 45% | |
| c) Tensile properties at maintained extension after water immersion | NPD | |
| d) Tensile properties at maintained extension | NPD | |
| e) Tensile properties at maintained extension at -30°C | NPD | |
| f) Tensile properties (secant modulus / elongation at break) | ≥25 % | |
| g) Tensile properties (secant modulus) at -30°C | NPD | |
| h) Durability | pass | |

**8.** The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

*Ville Aalto*

Product Manager
Rakennuskemia LTD
22.11.2021