

**DECLARATION OF PERFORMANCE - DOP**

#DOP23040/0757

1 / 2

Product name

**WTF Y Yes Flex**

- 1. Type of product**  
1 component MS hybrid polymer
- 2. Application**  
Sealant for the application in facades, glazing, sanitary and wet area joint and pedestrian walkways.  
Type F EXT-INT CC 20HM  
G CC 20HM  
S XS1  
PW EXT-INT CC 20HM  
Conditioning: Method B
- 3. Manufacturer / Importer**  
Rakennuskemia Oy, Kerkkolankatu 17, FIN-05800 Hyvinkää, Suomi
- 4. System of assessment of constancy of performance**  
3 plus 3
- 5. Harmonised Standard**  
EN 15651-1: 2012-12, EN 15651-2; 2012-12, EN 15651-3: 2012-12, EN 15651-4: 2012-12
- 6. Notified body**  
NB 0757, as notified laboratory in system 3, performed the initial test and issued the test report.

## DECLARATION OF PERFORMANCE - DOP

#DOP23040/0757

2 / 2

### 7. Essential characteristics

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 15651-1: 2012-12, EN 15651-2: 2012-12, EN 15651-3: 2012-12, EN 15651-4: 2012-12
Release of chemicals dangerous to the environment and health	Evaluated	
Water tightness and air tightness		
a) Resistance to flow	≤ 3mm	
b) Loss of volume	≤ 10%	
c) Elastic Recovery	≥60 %	
d) Tensile properties at maintained extension after water immersion	NF	
e) Tensile properties at maintained extension	NF	
f) Tensile properties at maintained extension at -30 oC	NF	
g) Tensile properties (secant modulus / elongation at break)	>0,4 MPa	
h) Tensile properties (secant modulus) at -30°C	NPD	
i) Adhesion/cohesion properties after exposure to heat, water and artificial light	NF	
j) Adhesion/cohesion properties at maintained extension after 28 days water immersion	NF	
k) Adhesion/cohesion properties at maintained extension after 28 days salt water immersion	NF	
l) Microbiological growth	1	
m) Tear resistance	NF	
n) Durability	pass	

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

*Ville Aalto*

Product Manager  
Rakennuskemia LTD  
22.11.2021