

DECLARATION OF PERFORMANCE - DOP

#DOP23320/0074

1 / 2

Product name

WTF A Acrylic Flex

- 1. Type of product**
1 component acrylic sealant
- 2. Application**
Façade Sealant for the application inside and outside
EN 15651-1: Type F EXT-INT 12,5P
- 3. Manufacturer / Importer**
Rakennuskemia LTD, Kerkkolankatu 17, FIN-05800 Hyvinkää. Finland
- 4. System of assessment of constancy of performance**
3 plus 3
- 5. Harmonised Standard**
EN 15651-1: 2012-12
- 6. 7. Notified body**
NB 0074, as notified laboratory in system 3, performed the initial test and issued the test report.
- 7. When dealing with DOP for construction product, of what an European technical assessment is given:**
Not applicable
- 8. Essential characteristics**
EN 15651-1:2012
Pretreatment: Method A (ISO 8339)
Substrate: Aluminium, Mortar

DECLARATION OF PERFORMANCE - DOP

#DOP23320/0074

2 / 2

Essential characteristics	Performance	Harmonisoitu tekninen spesifikaatio
Reaction to fire	Class E	EN 15651-1: 2012-12, EN 15651-3: 2012-12, EN 15651-4: 2012-12
Release of chemicals dangerous to the environment and health	not determined	
Water tightness and air tightness		
a) Resistance to flow	≤ 3mm	
b) Loss of volume	≤ 25%	
c) Elastic Recovery	≥40 %	
Tensile properties at stress in cold climates (-30 °C)	not demanded	
Secant modulus at -30°C (N/mm ²)	not demanded	
Adhesion on standard temperature	NF	
Adhesion/cohesion properties at maintained extension after water immersion	NF	
Elongation at break	>100%	
Elongation at break after water exposure	≥100 %	
Durability	Pass	

9. The performance of the product identified in the beginning is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Ville Aalto

Product Manager
Rakennuskemia LTD
24.11.2022