



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** MAXX GEAR Bolt-Off 360 Penetration Spray
- Other means of identification:**
EAN: 6418091140118
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Aerosol can product for recreational and decorative purposes
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Rakennuskemia Oy
Kerkkolankatu 17
05800 Hyvinkää - Finland
Phone: +358 19 4574400
info@rakennuskemia.com
www.rakennuskemia.com
- 1.4 Emergency telephone number:**

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):
Classification of this product has been carried out in accordance with GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).
Aerosol 1: Flammable aerosols, Category 1, H222
Aerosol 1: Pressurised container: May burst if heated., H229
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
Carc. 2: Carcinogenicity, Category 2, H351
Eye Irrit. 2: Eye irritation, Category 2, H319
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):
Danger
-
- Hazard statements:**
Aerosol 1: H222 - Extremely flammable aerosol.
Aerosol 1: H229 - Pressurised container: May burst if heated.
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Carc. 2: H351 - Suspected of causing cancer (Inhalation).
Eye Irrit. 2: H319 - Causes serious eye irritation.
STOT SE 3: H336 - May cause drowsiness or dizziness.
- Precautionary statements:**
P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.
P501: Dispose of the contents and/or its container using the separate collection system in your municipality.
- Supplementary information:**
EUH066: Repeated exposure may cause skin dryness or cracking.
- Additional labeling:**
Buildup of explosive mixtures possible without sufficient ventilation.

- CONTINUED ON NEXT PAGE -



SECTION 2: HAZARDS IDENTIFICATION (continued)

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture of substances

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: Non-applicable	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics Asp. Tox. 1: H304; EUH066 - Danger	25 - <50 %
CAS: 64742-55-8	Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 Asp. Tox. 1: H304 - Danger	20 - <25 %
CAS: 109-66-0	pentane Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	12.5 - <20 %
CAS: 74-98-6	Propane Flam. Gas 1A: H220; Press. Gas: H280 - Danger	5 - <10 %
CAS: 106-97-8	Butane (containing ≥ 0,1 % butadiene (203-450-8)) Carc. 1A: H350; Flam. Gas 1A: H220; Muta. 1B: H340; Press. Gas: H280 - Danger	5 - <10 %
CAS: 75-28-5	Isobutane (containing ≥ 0,1 % butadiene (203-450-8)) Carc. 1A: H350; Flam. Gas 1A: H220; Muta. 1B: H340; Press. Gas (Liq.): H280 - Danger	5 - <10 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

- CONTINUED ON NEXT PAGE -



SECTION 4: FIRST AID MEASURES (continued)

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

- CONTINUED ON NEXT PAGE -



SECTION 7: HANDLING AND STORAGE (continued)

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Occupational exposure limits		
	WEL (8h)	600 ppm	1800 mg/m ³
pentane CAS: 109-66-0	WEL (15 min)		
Butane (containing ≥ 0,1 % butadiene (203-450-8)) CAS: 106-97-8	WEL (8h)	600 ppm	1450 mg/m ³
	WEL (15 min)	750 ppm	1810 mg/m ³

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 CAS: 64742-55-8 EC: 265-158-7	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	Not relevant	5.58 mg/m ³
pentane CAS: 109-66-0 EC: 203-692-4	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	432 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	3000 mg/m ³	Not relevant

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 CAS: 64742-55-8 EC: 265-158-7	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	Not relevant	1.19 mg/m ³
pentane CAS: 109-66-0 EC: 203-692-4	Oral	Not relevant	Not relevant	214 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	214 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	643 mg/m ³	Not relevant

PNEC:

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 CAS: 64742-55-8 EC: 265-158-7	STP	Not relevant	Fresh water	Not relevant
	Soil	Not relevant	Marine water	Not relevant
	Intermittent	Not relevant	Sediment (Fresh water)	Not relevant
	Oral	9.33 g/kg	Sediment (Marine water)	Not relevant
pentane CAS: 109-66-0 EC: 203-692-4	STP	3.6 mg/L	Fresh water	0.23 mg/L
	Soil	0.55 mg/kg	Marine water	0.23 mg/L
	Intermittent	0.88 mg/L	Sediment (Fresh water)	1.2 mg/kg
	Oral	Not relevant	Sediment (Marine water)	1.2 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Remarks
 Compulsory use of face mask	Filter mask for particles	Replace when an increase in resistance to breathing is observed.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
 Mandatory hand protection	NON-disposable chemical protective gloves	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
 Mandatory face protection	Face shield	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection



Pictogram	PPE	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	Replace boots at any sign of deterioration.

F.- Additional emergency measures

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:

V.O.C. (Supply):	70.13 % weight
V.O.C. density at 20 °C:	Not relevant

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Aerosol
Appearance:	Not available
Colour:	According to the markings on the package
Odour:	Solvent
Odour threshold:	Not relevant *

Volatility:

Boiling point at atmospheric pressure:	Not relevant *
Vapour pressure at 20 °C:	349998 Pa
Vapour pressure at 50 °C:	Not relevant *
Evaporation rate at 20 °C:	Not relevant *

Product description:

Density at 20 °C:	Not relevant *
Relative density at 20 °C:	0.7
Dynamic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	Not relevant *
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Insoluble in water
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *
Recipient pressure:	Not relevant *

Flammability:

Flash Point:	Non-applicable
Flammability (solid, gas):	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Autoignition temperature: 285 °C (Propellant)
Lower flammability limit: 0.6 % Volume
Upper flammability limit: 8 % Volume

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Not relevant *
Oxidising properties: Not relevant *
Corrosive to metals: Not relevant *
Heat of combustion: Not relevant *
Aerosols-total percentage (by mass) of flammable components: Not relevant *

Other safety characteristics:

Surface tension at 20 °C: Not relevant *
Refraction index: Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- CONTINUED ON NEXT PAGE -



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
IARC: Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 (3)
 - Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
Propane CAS: 74-98-6	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L	
Butane (containing ≥ 0,1 % butadiene (203-450-8)) CAS: 106-97-8	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	658 mg/L (4 h)	Rat
Isobutane (containing ≥ 0,1 % butadiene (203-450-8)) CAS: 75-28-5	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics CAS: Non-applicable	LD50 oral	15000 mg/kg	Rat
	LD50 dermal	3160 mg/kg	Rat
	LC50 inhalation	>20 mg/L	

- CONTINUED ON NEXT PAGE -



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
pentane CAS: 109-66-0	>5000 mg/kg	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 CAS: 64742-55-8	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	>5000 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L (4 h)	Rat

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
	LC50	EC50		
Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 CAS: 64742-55-8	5000 mg/L (96 h)	1000 mg/L (48 h)	Oncorhynchus mykiss	Fish
	EC50	1000 mg/L (96 h)	Daphnia magna	Crustacean
	EC50	1000 mg/L (96 h)	Scenedesmus subspicatus	Algae
pentane CAS: 109-66-0	LC50	>1 - 10 mg/L (96 h)		Fish
	EC50	>1 - 10 mg/L (48 h)		Crustacean
	EC50	>1 - 10 mg/L (72 h)		Algae

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
	BOD5	COD	Concentration	Period
pentane CAS: 109-66-0	Not relevant	Not relevant	100 mg/L	28 days
	BOD5/COD	Not relevant	% Biodegradable	96 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
	BCF	Pow Log
Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 CAS: 64742-55-8		3.9
	Potential	
pentane CAS: 109-66-0	171	3.39
	Potential	High
Propane CAS: 74-98-6	13	2.86
	Potential	Low
Butane (containing ≥ 0,1 % butadiene (203-450-8)) CAS: 106-97-8	33	2.89
	Potential	Moderate

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
	Koc	Conclusion	Henry	Dry soil
pentane CAS: 109-66-0	80	Very High	126656.25 Pa·m ³ /mol	Yes
	Surface tension	1.547E-2 N/m (25 °C)	Moist soil	Yes
Propane CAS: 74-98-6	460	Moderate	71636.78 Pa·m ³ /mol	Yes
	Surface tension	7.02E-3 N/m (25 °C)	Moist soil	Yes

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volatility	
	Koc	Not relevant	Henry	Not relevant
Butane (containing $\geq 0,1$ % butadiene (203-450-8)) CAS: 106-97-8	Conclusion	Not relevant	Dry soil	Not relevant
	Surface tension	1.187E-2 N/m (25 °C)	Moist soil	Not relevant
	Koc	Not relevant	Henry	Not relevant
Isobutane (containing $\geq 0,1$ % butadiene (203-450-8)) CAS: 75-28-5	Conclusion	Not relevant	Dry soil	Not relevant
	Surface tension	9.84E-3 N/m (25 °C)	Moist soil	Not relevant
	Koc	Not relevant	Henry	Not relevant

Insoluble in water

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	Hazardous

Type of waste:

HP3 Flammable, HP14 Ecotoxic

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



- 14.1 UN number:** UN1950
14.2 UN proper shipping name: AEROSOLS
14.3 Transport hazard class(es): 2
 Labels: 2.1
14.4 Packing group: N/A
14.5 Environmental hazards: No
14.6 Special precautions for user
 Tunnel restriction code: D
 Physico-Chemical properties: see section 9
 Limited quantities: 1 L
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 41-22:

- CONTINUED ON NEXT PAGE -



SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number:	UN1950
14.2 UN proper shipping name:	AEROSOLS
14.3 Transport hazard class(es):	2
Labels:	2.1
14.4 Packing group:	N/A
14.5 Marine pollutant:	No
14.6 Special precautions for user	
Special regulations:	63, 959, 190, 277, 327, 344
EmS Codes:	F-D, S-U
Physico-Chemical properties:	see section 9
Limited quantities:	1 L
Segregation group:	Not relevant
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:	Not relevant

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:



14.1 UN number:	UN1950
14.2 UN proper shipping name:	AEROSOLS
14.3 Transport hazard class(es):	2
Labels:	2.1
14.4 Packing group:	N/A
14.5 Environmental hazards:	No
14.6 Special precautions for user	
Physico-Chemical properties:	see section 9
14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:	Not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Not relevant
- Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

The Control of Major Accident Hazards Regulations 2015:

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a	FLAMMABLE AEROSOLS	150	500

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.
The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.
Control of Substances Hazardous to Health Regulations 2002 (as amended)
EH40/2005 Workplace exposure limits.

- CONTINUED ON NEXT PAGE -

**SECTION 16: OTHER INFORMATION****Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 2:

H222: Extremely flammable aerosol.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
H412: Harmful to aquatic life with long lasting effects.
H229: Pressurised container: May burst if heated.
H351: Suspected of causing cancer (Inhalation).

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
Carc. 1A: H350 - May cause cancer.
Flam. Gas 1A: H220 - Extremely flammable gas.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Muta. 1B: H340 - May cause genetic defects.
Press. Gas (Liq.): H280 - Contains gas under pressure, may explode if heated.
Press. Gas: H280 - Contains gas under pressure, may explode if heated.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -