

MAXX GEAR Motor QuickStart 200ml



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: MAXX GEAR Motor QuickStart 200ml

Other means of identification:

EAN: 6418091140231

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Oil and gas exploration or production products

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Rakennuskemia Oy Kerkkolankatu 17 05800 Hyvinkää - Finland Phone: +358 19 4574400 info@rakennuskemia.com

www.rakennuskemia.com

1.4 Emergency telephone number: Telephone NHS 111 (England), NHS 24 (Scotland) or NHS Direct (Wales).

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Classification of this product has been carried out in accordance with GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).

Aerosol 1: Flammable aerosols, Category 1, H222

Aerosol 1: Pressurised container: May burst if heated., H229

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411

Skin Irrit. 2: Skin irritation, Category 2, H315

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Danger







Hazard statements:

Aerosol 1: H222 - Extremely flammable aerosol.

Aerosol 1: H229 - Pressurised container: May burst if heated.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.

P501: Dispose of the contents and/or its container using the separate collection system in your municipality.

Additional labeling:

Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards:

Product does not meet PBT/vPvB criteria



MAXX GEAR Motor QuickStart 200ml



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture of substances

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

	Identification	Chemical name/Classification	Concentration
CAS:	115-10-6	Dimethyl ether Flam. Gas 1A: H220; Press. Gas: H280 - Danger	50 - <75 %
CAS:	Non-applicable	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 - Danger	20 - <25 %
CAS:	74-98-6	Propane Flam. Gas 1A: H220; Press. Gas: H280 - Danger	12.5 - <20 %
CAS:	75-28-5	Isobutane (containing ≥ 0,1 % butadiene (203-450-8)) Carc. 1A: H350; Flam. Gas 1A: H220; Muta. 1B: H340; Press. Gas (Liq.): H280 - Danger	5 - <10 %
CAS:	106-97-8	Butane (containing ≥ 0,1 % butadiene (203-450-8)) Carc. 1A: H350; Flam. Gas 1A: H220; Muta. 1B: H340; Press. Gas: H280 - Danger	5 - <10 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

Bv inhalation

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply,etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

MAX(° GEAR

Safety data sheet According to UK REACH (S.I. 2019/758)

MAXX GEAR Motor QuickStart 200ml



SECTION 5: FIREFIGHTING MEASURES (continued)

5.1 Extinguishing media:

Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

- CONTINUED ON NEXT PAGE -

Date of compilation: 15/07/2024 Revised: 15/07/2024 Version: 2 (Replaced 1) **Page 3/12**



MAXX GEAR Motor QuickStart 200ml



SECTION 7: HANDLING AND STORAGE (continued)

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Occupational exposure limits		
Dimethyl ether	WEL (8h)	400 ppm	766 mg/m ³
CAS: 115-10-6	WEL (15 min)	500 ppm	958 mg/m ³
Butane (containing ≥ 0,1 % butadiene (203-450-8))	WEL (8h)	600 ppm	1450 mg/m ³
CAS: 106-97-8	WEL (15 min)	750 ppm	1810 mg/m ³

Oils: WEL (15 min)= 10 mg/m3

DNEL (Workers):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Dimethyl ether	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 115-10-6	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 204-065-8	Inhalation	Not relevant	Not relevant	1894 mg/m ³	Not relevant
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: Non-applicable	Dermal	Not relevant	Not relevant	773 mg/kg	Not relevant
EC: 921-024-6	Inhalation	Not relevant	Not relevant	2035 mg/m ³	Not relevant

DNEL (General population):

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
Dimethyl ether	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 115-10-6	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 204-065-8	Inhalation	Not relevant	Not relevant	471 mg/m³	Not relevant
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Oral	Not relevant	Not relevant	699 mg/kg	Not relevant
CAS: Non-applicable	Dermal	Not relevant	Not relevant	699 mg/kg	Not relevant
EC: 921-024-6	Inhalation	Not relevant	Not relevant	608 mg/m ³	Not relevant

PNEC:

Identification				
Dimethyl ether	STP	160 mg/L	Fresh water	0.155 mg/L
CAS: 115-10-6	Soil	0.045 mg/kg	Marine water	0.016 mg/L
EC: 204-065-8	Intermittent	1.549 mg/L	Sediment (Fresh water)	0.681 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0.069 mg/kg

8.2 Exposure controls:



MAXX GEAR Motor QuickStart 200ml



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Remarks
Mandatory respiratory tract protection	Filter mask for gases, vapours and particles	Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	Protective gloves against minor risks	Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN ISO 21420:2020 and EN ISO 374-1:2016+ A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Remarks
Mandatory complete body protection	Antistatic and fireproof protective clothing	Limited protection against flames.
Mandatory foot protection	Safety footwear with antistatic and heat resistant properties	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
*	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	*	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:

V.O.C. (Supply): 100 % weight V.O.C. density at 20 °C: Not relevant



MAXX GEAR Motor QuickStart 200ml



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Colour:

Colour:

Ethereal

Odour threshold:

Not relevant *

Volatility:

Boiling point at atmospheric pressure: Not relevant * Vapour pressure at 20 °C: 829999 Pa

Vapour pressure at 50 °C: <300000 Pa (300 kPa)

Evaporation rate at 20 °C: Not relevant *

Product description:

Density at 20 °C: Not relevant *

Relative density at 20 °C: 0.6

Dynamic viscosity at 20 °C: Not relevant * Kinematic viscosity at 20 °C: Not relevant * Kinematic viscosity at 40 °C: Not relevant * Concentration: Not relevant * pH: Not relevant * Vapour density at 20 °C: Not relevant * Partition coefficient n-octanol/water 20 °C: Not relevant * Solubility in water at 20 °C: Not relevant * Solubility properties: Insoluble in water Not relevant * Decomposition temperature: Melting point/freezing point: Not relevant * Recipient pressure: Not relevant *

Flammability:

Flash Point:

Flammability (solid, gas):

Autoignition temperature:

Lower flammability limit:

Upper flammability limit:

Non-applicable

Not relevant *

200 °C (Propellant)

0.6 % Volume

26.2 % Volume

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable

Not relevant *

Not relevant *

Not relevant *

components:

*Not relevant due to the nature of the product, not providing information property of its hazards.



MAXX GEAR Motor QuickStart 200ml



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Other safety characteristics:

Surface tension at 20 °C:

Not relevant *

Refraction index:

Not relevant *

VOC (EC) 636.0 g/l VOC-EU% 100 %

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

MAX(° GEAR

Safety data sheet According to UK REACH (S.I. 2019/758)

MAXX GEAR Motor QuickStart 200ml



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.

 IARC: Not relevant
 - Mutagenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with mutagenic effects. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Dimethyl ether	LD50 oral	>5000 mg/kg	
CAS: 115-10-6	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	308.5 mg/L (4 h)	Rat
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	LD50 oral	5840 mg/kg	Rat
CAS: Non-applicable	LD50 dermal	2920 mg/kg	Rat
	LC50 inhalation	>20 mg/L	
Propane	LD50 oral	>5000 mg/kg	
CAS: 74-98-6	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L	
Butane (containing ≥ 0,1 % butadiene (203-450-8))	LD50 oral	>5000 mg/kg	
CAS: 106-97-8	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	658 mg/L (4 h)	Rat
Isobutane (containing ≥ 0,1 % butadiene (203-450-8))	LD50 oral	>5000 mg/kg	
CAS: 75-28-5	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available Toxic to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:



MAXX GEAR Motor QuickStart 200ml



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	LC50	5.1 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: Non-applicable		Not relevant		
	EC50	Not relevant		

Chronic toxicity:

Identification	Concentration		Species	Genus
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	NOEC	Not relevant		
CAS: Non-applicable	NOEC	0.17 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	BOD5	Not relevant	Concentration	Not relevant
CAS: Non-applicable	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	98 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential		
Propane	BCF	13	
CAS: 74-98-6	Pow Log	2.86	
	Potential	Low	
Butane (containing ≥ 0,1 % butadiene (203-450-8))	BCF	33	
CAS: 106-97-8	Pow Log	2.89	
	Potential	Moderate	

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Dimethyl ether	Koc	Not relevant	Henry	Not relevant
CAS: 115-10-6	Conclusion	Not relevant	Dry soil	Not relevant
	Surface tension	1.136E-2 N/m (25 °C)	Moist soil	Not relevant
Isobutane (containing ≥ 0,1 % butadiene (203-450-8))	Koc	Not relevant	Henry	Not relevant
CAS: 75-28-5	Conclusion	Not relevant	Dry soil	Not relevant
	Surface tension	9.84E-3 N/m (25 °C)	Moist soil	Not relevant
Propane	Koc	460	Henry	71636.78 Pa·m³/mol
CAS: 74-98-6	Conclusion	Moderate	Dry soil	Yes
	Surface tension	7.02E-3 N/m (25 °C)	Moist soil	Yes
Butane (containing ≥ 0,1 % butadiene (203-450-8))	Koc	Not relevant	Henry	Not relevant
CAS: 106-97-8	Conclusion	Not relevant	Dry soil	Not relevant
	Surface tension	1.187E-2 N/m (25 °C)	Moist soil	Not relevant

Insoluble in water

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	Hazardous

MAXX GEAR Motor QuickStart 200ml



SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Type of waste:

HP3 Flammable, HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:





UN1950 14.1 UN number: 14.2 UN proper shipping name: **AEROSOLS**

14.3 Transport hazard class(es): Labels: 2.1 14.4 Packing group: N/A

14.5 Environmental hazards: Yes 14.6 Special precautions for user

Tunnel restriction code: D

> Physico-Chemical properties: see section 9

Limited quantities: 1 L

14.7 Transport in bulk according Not relevant

to Annex II of Marpol and the IBC Code:

Transport of dangerous goods by sea:

With regard to IMDG 41-22:

UN1950 14.1 UN number:

14.2 UN proper shipping name: **AEROSOLS**

14.3 Transport hazard class(es): Labels: 2.1

14.4 Packing group: N/A 14.5 Marine pollutant: Yes

14.6 Special precautions for user

Special regulations: 63, 959, 190, 277, 327, 344

EmS Codes: F-D, S-U Physico-Chemical properties: see section 9

Limited quantities: 1 L

Not relevant Segregation group: 14.7 Transport in bulk according Not relevant

to Annex II of Marpol and the IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:

MAX(° GEAR

Safety data sheet According to UK REACH (S.I. 2019/758)

MAXX GEAR Motor QuickStart 200ml



SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number: UN1950

14.2 UN proper shipping name: AEROSOLS

14.3 Transport hazard class(es): 2 Labels: 2.1

14.4 Packing group: N/A
14.5 Environmental hazards: Yes

14.6 Special precautions for user

Physico-Chemical properties: see section 9 **14.7 Transport in bulk according** Not relevant

to Annex II of Marpol and

the IBC Code:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Not relevant
- Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

The Control of Major Accident Hazards Regulations 2015:

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a	FLAMMABLE AEROSOLS	150	500

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

The Aerosol Dispensers Regulations 2009

The Product Safety and Metrology etc. (Amendment etc.) (EU Exit) Regulations 2019: SCHEDULE 13 -Amendment of the Aerosol Dispensers Regulations 2009

The Product Safety and Metrology etc. (Amendment etc.) (UK(NI) Indication) (EU Exit) Regulations 2020

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 2:

H222: Extremely flammable aerosol.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

H229: Pressurised container: May burst if heated.

Texts of the legislative phrases mentioned in section 3:

MAX(° GEAR

Safety data sheet According to UK REACH (S.I. 2019/758)

MAXX GEAR Motor QuickStart 200ml



SECTION 16: OTHER INFORMATION (continued)

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Carc. 1A: H350 - May cause cancer.

Flam. Gas 1A: H220 - Extremely flammable gas.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Muta. 1B: H340 - May cause genetic defects.

Press. Gas (Liq.): H280 - Contains gas under pressure, may explode if heated.

Press. Gas: H280 - Contains gas under pressure, may explode if heated.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.