

### This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

#### **MAXX GEAR Lock Oil**



### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: MAXX GEAR Lock Oil

Other means of identification:

EAN: 6418091140255

**UFI:** 10XU-W82S-E30H-44ES

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Aerosol can product for recreational and decorative purposes Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Rakennuskemia Oy Kerkkolankatu 17 05800 Hyvinkää - Finland Phone: +358 19 4574400 info@rakennuskemia.com

www.rakennuskemia.com

1.4 Emergency telephone number: Emergency: 112. Poison information center Helsinki, open 24 h/day+358 9 471 977 (direct);

+358 9 4711 (central)

#### SECTION 2: HAZARDS IDENTIFICATION \*\*

#### 2.1 Classification of the substance or mixture:

#### CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aerosol 1: Pressurised container: May burst if heated., H229

Aerosol 1: Flammable aerosols, Category 1, H222

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

#### 2.2 Label elements:

### CLP Regulation (EC) No 1272/2008:

Danger



### **Hazard statements:**

Aerosol 1: H229 - Pressurised container: May burst if heated.

Aerosol 1: H222 - Extremely flammable aerosol.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

#### **Precautionary statements:**

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P260: Do not breathe spray.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F

P501: Dispose of contents / container in accordance with regional regulations.

### Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.

**UFI:** 10XU-W82S-E30H-44ES

### Additional labeling:

Buildup of explosive mixtures possible without sufficient ventilation.

### 2.3 Other hazards:

- CONTINUED ON NEXT PAGE -

<sup>\*\*</sup> Changes with regards to the previous version



### This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### **MAXX GEAR Lock Oil**



### SECTION 2: HAZARDS IDENTIFICATION \*\* (continued)

Product does not meet PBT/vPvB criteria

Endocrine-disrupting properties: The product does not meet the criteria.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS \*\*

#### 3.1 Substance:

Non-applicable

#### 3.2 Mixture:

Chemical description: Mixture of substances

**Components:** 

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification	Concentration		
CAS: EC:	64742-55-8 265-158-7	Distillates (petroleum), hydrotreated light paraffinic, Table 3 of Annex VI (Regulation no 1272/2008) < 3 % IP 346(1)				
Index: REACH:	649-468-00-3 01-2119487077-29- XXXX	Regulation 1272/2008	Asp. Tox. 1: H304 - Danger	20 - <25 %		
CAS: EC:	Non-applicable 918-481-9	Hydrocarbons, C10-0 <2% aromatics <sup>(1)</sup>	13, n-alkanes, isoalkanes, cyclics, Table 3 of Annex VI (Regulation nº 1272/2008)			
Index: REACH:	Non-applicable 01-2119457273-39- XXXX	Regulation 1272/2008	Asp. Tox. 1: H304; EUH066 - Danger	12.5 - <20 %		
CAS:			Table 3 of Annex VI (Regulation nº 1272/2008)			
EC: Index: REACH:	203-692-4 601-006-00-1 01-2119459286-30- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	12.5 - <20 %		
CAS:	74-98-6	Propane <sup>(2)</sup>	Table 3 of Annex VI (Regulation nº 1272/2008)			
EC: Index: REACH:	200-827-9 601-003-00-5 01-2119486944-21- XXXX	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger	12.5 - <20 %		
CAS: EC:	106-97-8 203-448-7	Butane (containing	<b>2 0,1 % butadiene (203-450-8))</b> (2) Table 3 of Annex VI (Regulation nº 1272/2008)			
Index:	203-448-7 601-004-01-8 01-2119474691-32- XXXX	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger	10 - <12.5 %		
CAS: EC: Index:	75-28-5 200-857-2	Isobutane (containir ) <sup>(2)</sup>	<b>ng ≥ 0,1 % butadiene (203-450-8)</b> Table 3 of Annex VI (Regulation nº 1272/2008)			
	601-004-01-8 01-2119485395-27- XXXX	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas (Liq.): H280 - Danger	5 - <10 %		

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878 (2) Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

### **SECTION 4: FIRST AID MEASURES**

#### 4.1 **Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/05/2019 Revised: 24/05/2024 Version: 3 (Replaced 2) Page 2/13

<sup>\*\*</sup> Changes with regards to the previous version

<sup>\*\*</sup> Changes with regards to the previous version



#### This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

#### **MAXX GEAR Lock Oil**



### SECTION 4: FIRST AID MEASURES (continued)

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

#### By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

#### By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

#### 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

#### 4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

### **SECTION 5: FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media:

#### Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

#### Unsuitable extinguishing media:

Water jet

#### 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

#### 5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

### **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

#### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures:

### For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

### For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

#### 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

### 6.3 Methods and material for containment and cleaning up:

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/05/2019 Revised: 24/05/2024 Version: 3 (Replaced 2) **Page 3/13** 



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

#### **MAXX GEAR Lock Oil**



### SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13.

### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

### 7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

### 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
pentane	IOELV (8h)	1000 ppm	3000 mg/m <sup>3</sup>
CAS: 109-66-0 EC: 203-692-4	IOELV (STEL)		

### **DNEL (Workers):**

		Short e	xposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
Distillates (petroleum), hydrotreated light paraffinic, $<$ 3 % IP 346	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 64742-55-8	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 265-158-7	Inhalation	Not relevant	Not relevant	Not relevant	5,58 mg/m <sup>3</sup>
pentane	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 109-66-0	Dermal	Not relevant	Not relevant	432 mg/kg	Not relevant
EC: 203-692-4	Inhalation	Not relevant	Not relevant	3000 mg/m <sup>3</sup>	Not relevant

- CONTINUED ON NEXT PAGE -



### This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### **MAXX GEAR Lock Oil**



### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

#### **DNEL (General population):**

		Short e	xposure	Long ex	xposure
Identification		Systemic	Local	Systemic	Local
Distillates (petroleum), hydrotreated light paraffinic, $<$ 3 % IP 346	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 64742-55-8	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 265-158-7	Inhalation	Not relevant	Not relevant	Not relevant	1,19 mg/m <sup>3</sup>
pentane	Oral	Not relevant	Not relevant	214 mg/kg	Not relevant
CAS: 109-66-0	Dermal	Not relevant	Not relevant	214 mg/kg	Not relevant
EC: 203-692-4	Inhalation	Not relevant	Not relevant	643 mg/m <sup>3</sup>	Not relevant

#### PNEC:

Identification				
Distillates (petroleum), hydrotreated light paraffinic, $<$ 3 $\%$ IP 346	STP	Not relevant	Fresh water	Not relevant
CAS: 64742-55-8	Soil	Not relevant	Marine water	Not relevant
EC: 265-158-7	Intermittent	Not relevant	Sediment (Fresh water)	Not relevant
	Oral	9,33 g/kg	Sediment (Marine water)	Not relevant
pentane	STP	3,6 mg/L	Fresh water	0,23 mg/L
CAS: 109-66-0	Soil	0,55 mg/kg	Marine water	0,23 mg/L
EC: 203-692-4	Intermittent	0,88 mg/L	Sediment (Fresh water)	1,2 mg/kg
	Oral	Not relevant	Sediment (Marine water)	1,2 mg/kg

#### 8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

## B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Compulsory use of face mask	Filter mask for particles	CAT III	EN 149:2001+A1:2009	Replace when an increase in resistence to breathing is observed.

### C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	CAT III	EN ISO 374-1:2016+A1:2018 EN 16523-1:2015+A1:2018 EN ISO 21420:2020	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

#### D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CATI	EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/05/2019 Revised: 24/05/2024 Version: 3 (Replaced 2) Page 5/13



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

#### **MAXX GEAR Lock Oil**



### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CAT III	EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

#### F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

#### **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

#### Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 61,8 % weight V.O.C. density at 20 °C: Not relevant

Average carbon number: 8,5

Average molecular weight: 101,1 g/mol

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

### Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Odour:

Odour threshold:

Aerosol

Not available

Brown

Characteristic

Not relevant \*

Volatility:

Boiling point at atmospheric pressure: Not relevant \* Vapour pressure at 20 °C: 349998 Pa

Vapour pressure at 50 °C: <300000 Pa (300 kPa)

Evaporation rate at 20 °C: Not relevant \*

**Product description:** 

Density at 20 °C: Not relevant \*

Relative density at 20 °C: 0,7

Dynamic viscosity at 20 °C: Not relevant \* Kinematic viscosity at 20 °C: Not relevant \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/05/2019 Revised: 24/05/2024 Version: 3 (Replaced 2) Page 6/13



 $\dot{\text{This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation}$ 

#### **MAXX GEAR Lock Oil**



### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Kinematic viscosity at 40 °C: Not relevant \* Concentration: Not relevant \* pH: Not relevant \* Vapour density at 20 °C: Not relevant \* Partition coefficient n-octanol/water 20 °C: Not relevant \* Solubility in water at 20 °C: Not relevant \* Solubility properties: Immiscible Not relevant \* Decomposition temperature: Melting point/freezing point: Not relevant \* Recipient pressure: Not relevant \*

Flammability:

Flash Point:

Flammability (solid, gas):

Autoignition temperature:

Lower flammability limit:

Upper flammability limit:

Non-applicable

Not relevant \*

200 °C (Propellant)

0,6 % Volume

10,9 % Volume

Particle characteristics:

Median equivalent diameter: Non-applicable

#### 9.2 Other information:

#### Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Not relevant \*

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable components:

Not relevant \*

Not relevant \*

Other safety characteristics:

Surface tension at 20 °C:

Refraction index:

Not relevant \*

Not relevant \*

VOC (EC) 461.9 g/l VOC-EU% 66.85 %

\*Not relevant due to the nature of the product, not providing information property of its hazards.

### SECTION 10: STABILITY AND REACTIVITY

#### 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

#### 10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

### 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

#### 10.5 Incompatible materials:

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/05/2019 Revised: 24/05/2024 Version: 3 (Replaced 2) Page 7/13



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

#### **MAXX GEAR Lock Oil**



### SECTION 10: STABILITY AND REACTIVITY (continued)

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

#### SECTION 11: TOXICOLOGICAL INFORMATION \*\*

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

#### **Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
  - Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
    - IARC: Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346 (3)
  - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.


- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
  - Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

\*\* Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/05/2019 Revised: 24/05/2024 Version: 3 (Replaced 2) **Page 8/13** 





This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### **MAXX GEAR Lock Oil**



### SECTION 11: TOXICOLOGICAL INFORMATION \*\* (continued)

#### Other information:

Not relevant

### Specific toxicology information on the substances:

Identification	Acu	te toxicity	Genus
Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346	LD50 oral	>5000 mg/kg	Rat
CAS: 64742-55-8	LD50 dermal	>5000 mg/kg	Rabbit
EC: 265-158-7	LC50 inhalation	>20 mg/L (4 h)	Rat
Propane	LD50 oral	>2000 mg/kg	
CAS: 74-98-6	LD50 dermal	>2000 mg/kg	
EC: 200-827-9	LC50 inhalation	>5 mg/L	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	LD50 oral	>2000 mg/kg	
CAS: Non-applicable	LD50 dermal	>2000 mg/kg	
EC: 918-481-9	LC50 inhalation	>20 mg/L	
pentane	LD50 oral	>2000 mg/kg	
CAS: 109-66-0	LD50 dermal	>2000 mg/kg	
EC: 203-692-4	LC50 inhalation	>20 mg/L	
Butane (containing ≥ 0,1 % butadiene (203-450-8))	LD50 oral	>2000 mg/kg	
CAS: 106-97-8	LD50 dermal	>2000 mg/kg	
EC: 203-448-7	LC50 inhalation	658 mg/L (4 h)	Rat
Isobutane (containing ≥ 0,1 % butadiene (203-450-8))	LD50 oral	>2000 mg/kg	
CAS: 75-28-5	LD50 dermal	>2000 mg/kg	
EC: 200-857-2	LC50 inhalation	>5 mg/L	•

### **Acute Toxicity Estimate (ATE mix):**

ATE mix		Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	Non-applicable
Dermal	>2000 mg/kg (Calculation method)	Non-applicable
Inhalation	>20 mg/L (4 h) (Calculation method)	Non-applicable

#### 11.2 Information on other hazards:

#### **Endocrine disrupting properties**

Endocrine-disrupting properties: The product does not meet the criteria.

### Other information

Not relevant

### SECTION 12: ECOLOGICAL INFORMATION \*\*

The experimental information related to the eco-toxicological properties of the product itself is not available Harmful to aquatic life with long lasting effects.

### 12.1 Toxicity:

### Acute toxicity:

Identification	Concentration		Species	Genus
Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346	LC50	5000 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 64742-55-8	EC50	1000 mg/L (48 h)	Daphnia magna	Crustacean
EC: 265-158-7	EC50	1000 mg/L (96 h)	Scenedesmus subspicatus	Algae
pentane	LC50	Not relevant		
CAS: 109-66-0	EC50	9,74 mg/L (48 h)	Daphnia magna	Crustacean
EC: 203-692-4	EC50	Not relevant		

### 12.2 Persistence and degradability:

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/05/2019 Revised: 24/05/2024 Version: 3 (Replaced 2) Page 9/13

<sup>\*\*</sup> Changes with regards to the previous version

<sup>\*\*</sup> Changes with regards to the previous version



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

### **MAXX GEAR Lock Oil**



### SECTION 12: ECOLOGICAL INFORMATION \*\* (continued)

#### **Substance-specific information:**

Identification	Degradability		Biodegradability	
pentane	BOD5	Not relevant	Concentration	100 mg/L
CAS: 109-66-0	COD	Not relevant	Period	28 days
EC: 203-692-4	BOD5/COD	Not relevant	% Biodegradable	96 %

### 12.3 Bioaccumulative potential:

#### **Substance-specific information:**

Identification	Bioaccumulation potential	
Distillates (petroleum), hydrotreated light paraffinic, < 3 % IP 346	BCF	
CAS: 64742-55-8	Pow Log	3.9
EC: 265-158-7	Potential	
pentane	BCF	171
CAS: 109-66-0	Pow Log	3.39
EC: 203-692-4	Potential	High
Propane	BCF	13
CAS: 74-98-6	Pow Log	2.86
EC: 200-827-9	Potential	Low
Butane (containing ≥ 0,1 % butadiene (203-450-8))	BCF	33
CAS: 106-97-8	Pow Log	2.89
EC: 203-448-7	Potential	Moderate

### 12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
pentane	Koc	80	Henry	126656,25 Pa·m³/mol
CAS: 109-66-0	Conclusion	Very High	Dry soil	Yes
EC: 203-692-4	Surface tension	1,547E-2 N/m (25 °C)	Moist soil	Yes
Propane	Koc	460	Henry	71636,78 Pa·m³/mol
CAS: 74-98-6	Conclusion	Moderate	Dry soil	Yes
EC: 200-827-9	Surface tension	7,02E-3 N/m (25 °C)	Moist soil	Yes
Butane (containing ≥ 0,1 % butadiene (203-450-8))	Koc	Not relevant	Henry	Not relevant
CAS: 106-97-8	Conclusion	Not relevant	Dry soil	Not relevant
EC: 203-448-7	Surface tension	1,187E-2 N/m (25 °C)	Moist soil	Not relevant
Isobutane (containing ≥ 0,1 % butadiene (203-450-8))	Koc	Not relevant	Henry	Not relevant
CAS: 75-28-5	Conclusion	Not relevant	Dry soil	Not relevant
EC: 200-857-2	Surface tension	9,84E-3 N/m (25 °C)	Moist soil	Not relevant

### 12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

## 12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

### 12.7 Other adverse effects:

Not described

### **SECTION 13: DISPOSAL CONSIDERATIONS**

## 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	Hazardous

### Type of waste (Regulation (EU) No 1357/2014):

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/05/2019 Revised: 24/05/2024 Version: 3 (Replaced 2) Page 10/13

<sup>\*\*</sup> Changes with regards to the previous version



### This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

#### **MAXX GEAR Lock Oil**



### SECTION 13: DISPOSAL CONSIDERATIONS (continued)

HP14 Ecotoxic, HP3 Flammable

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

#### Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

### **SECTION 14: TRANSPORT INFORMATION**

#### Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



14.1 UN number or ID number: UN195014.2 UN proper shipping name: AEROSOLS

 14.3
 Transport hazard class(es):
 2

 Labels:
 2.1

 14.4
 Packing group:
 N/A

14.5 Environmental hazards: No

14.6 Special precautions for user

Special regulations: 190, 327, 344, 625

Tunnel restriction code: D

Physico-Chemical properties: see section 9

Limited quantities: 1 L

14.7 Maritime transport in bulk

according to IMO instruments:

Not relevant

#### Transport of dangerous goods by sea:

With regard to IMDG 41-22:



14.1 UN number or ID number: UN195014.2 UN proper shipping name: AEROSOLS

**14.3** Transport hazard class(es): 2 Labels: 2.1

14.4Packing group:N/A14.5Marine pollutant:No

14.6 Special precautions for user

Special regulations: 63, 959, 190, 277, 327, 344

EmS Codes: F-D, S-U
Physico-Chemical properties: see section 9

Limited quantities: 1 L

Segregation group: Not relevant **14.7 Maritime transport in bulk** Not relevant

according to IMO instruments:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/05/2019 Revised: 24/05/2024 Version: 3 (Replaced 2) Page 11/13



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

#### **MAXX GEAR Lock Oil**



### SECTION 14: TRANSPORT INFORMATION (continued)



14.1 UN number or ID number: UN195014.2 UN proper shipping name: AEROSOLS

**14.3** Transport hazard class(es): 2

Labels: 2.1

Packing group: N/A

**14.4 Packing group:** N/A **14.5 Environmental hazards:** No

14.6 Special precautions for user

Physico-Chemical properties: see section 9

Maritime transport in bulk Not relevant

14.7 Maritime transport in bulk according to IMO

instruments:

## SECTION 15: REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

#### Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a	FLAMMABLE AEROSOLS	150	500

# Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

### Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

### Other legislation:

The product could be affected by sectorial legislation

#### 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

### **SECTION 16: OTHER INFORMATION**

### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

### Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMPOSITION/INFORMATION ON INGREDIENTS (SECTION 3, SECTION 11, SECTION 12):

· New declared substances

Butane (containing  $\geq$  0,1 % butadiene (203-450-8)) (106-97-8) Isobutane (containing  $\geq$  0,1 % butadiene (203-450-8)) (75-28-5)

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

· Precautionary statements

### Texts of the legislative phrases mentioned in section 2:

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/05/2019 Revised: 24/05/2024 Version: 3 (Replaced 2) Page 12/13



### This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

#### **MAXX GEAR Lock Oil**



### SECTION 16: OTHER INFORMATION (continued)

H412: Harmful to aquatic life with long lasting effects.

H229: Pressurised container: May burst if heated.

H222: Extremely flammable aerosol.

### Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

### CLP Regulation (EC) No 1272/2008:

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Flam. Gas 1A: H220 - Extremely flammable gas.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Press. Gas (Liq.): H280 - Contains gas under pressure, may explode if heated.

Press. Gas: H280 - Contains gas under pressure, may explode if heated.

STOT SE 3: H336 - May cause drowsiness or dizziness.

#### Classification procedure:

Aquatic Chronic 3: Calculation method Aerosol 1: Calculation method Aerosol 1: Calculation method

#### Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

#### Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

#### **Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.