

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: MAXX GEAR Primer Grey 400ml

Other means of identification:

EAN: 6418091140682

UFI: 8N3W-08T9-630T-MW8A

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Aerosol can product for recreational and decorative purposes

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Rakennuskemia Oy
Kerkkolankatu 17
05800 Hyvinkää - Finland
Phone: +358 19 4574400
info@rakennuskemia.com
www.rakennuskemia.com

1.4 Emergency telephone number: Emergency: 112. Poison information center Helsinki, open 24 h/day+358 9 471 977 (direct); +358 9 4711 (central)

SECTION 2: HAZARDS IDENTIFICATION **

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aerosol 1: Flammable aerosols, Category 1, H222
Aerosol 1: Pressurised container: May burst if heated., H229
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
Eye Irrit. 2: Eye irritation, Category 2, H319
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger



Hazard statements:

Aerosol 1: H222 - Extremely flammable aerosol.
Aerosol 1: H229 - Pressurised container: May burst if heated.
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Eye Irrit. 2: H319 - Causes serious eye irritation.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P260: Do not breathe spray.
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F
P501: Dispose of contents / container in accordance with regional regulations.

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.
EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

UFI: 8N3W-08T9-630T-MW8A

*** Changes with regards to the previous version*

- CONTINUED ON NEXT PAGE -



SECTION 2: HAZARDS IDENTIFICATION ** (continued)

Additional labeling:

Hazard-determining components of labelling:
acetone
n-butyl acetate
2-methoxy-1-methylethyl acetate
butan-1-ol
Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards:

Product does not meet PBT/vPvB criteria
Endocrine-disrupting properties: The product does not meet the criteria.

*** Changes with regards to the previous version*

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture of substances

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 67-64-1 EC: 200-662-2 Index: 606-001-00-8 REACH: 01-2119471330-49-XXXX	**acetone(1)**	ATP CLP00	**25 - <50 %**
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger 	
CAS: 115-10-6 EC: 204-065-8 Index: 603-019-00-8 REACH: 01-2119472128-37-XXXX	**Dimethyl ether(2)**	ATP CLP00	**12.5 - <20 %**
	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger 	
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	**N-butyl acetate(1)**	ATP CLP00	**10 - <12.5 %**
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning 	
CAS: 108-65-6 EC: 203-603-9 Index: 607-195-00-7 REACH: 01-2119475791-29-XXXX	**2-methoxy-1-methylethyl acetate(2)**	ATP ATP01	**5 - <10 %**
	Regulation 1272/2008	Flam. Liq. 3: H226 - Warning 	
CAS: 74-98-6 EC: 200-827-9 Index: 601-003-00-5 REACH: 01-2119486944-21-XXXX	**Propane(3)**	Table 3 of Annex VI (Regulation nº 1272/2008)	**5 - <10 %**
	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger 	
CAS: 106-97-8 EC: 203-448-7 Index: 601-004-01-8 REACH: 01-2119474691-32-XXXX	**Butane (containing ≥ 0,1 % butadiene (203-450-8))(3)**	Table 3 of Annex VI (Regulation nº 1272/2008)	**5 - <10 %**
	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger 	
CAS: 75-28-5 EC: 200-857-2 Index: 601-004-01-8 REACH: 01-2119485395-27-XXXX	**Isobutane (containing ≥ 0,1 % butadiene (203-450-8))(3)**	Table 3 of Annex VI (Regulation nº 1272/2008)	**5 - <10 %**
	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas (Liq.): H280 - Danger 	
CAS: 13463-67-7 EC: 236-675-5 Index: 022-006-002 REACH: 01-2119489379-17-XXXX	**Titanium dioxide(1)**	Self-classified	**2.5 - <5 %**
	Regulation 1272/2008	Carc. 2: H351 - Warning 	

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878
(2) Substance with a Union workplace exposure limit
(3) Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878

- CONTINUED ON NEXT PAGE -



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Chemical name/Classification		Concentration
CAS: 9004-70-0 EC: 682-719-5 Index: 603-037-00-6 REACH: Non-applicable	**Cellulose nitrate**(3)	Table 3 of Annex VI (Regulation nº 1272/2008)	**<2.5 %**
	Regulation 1272/2008	Expl. 1.1: H201 - Danger	
CAS: 71-36-3 EC: 200-751-6 Index: 603-004-00-6 REACH: 01-2119484630-38-XXXX	**butan-1-ol**(1)	ATP CLP00	**<2.5 %**
	Regulation 1272/2008	Acute Tox. 4: H302; Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335; STOT SE 3: H336 - Danger	
CAS: 7779-90-0 EC: 231-944-3 Index: Non-applicable REACH: 01-2119485044-40-XXXX	**trizinc bis(orthophosphate)**(1)	ATP CLP00	**<2.5 %**
	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410 - Warning	

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878
(2) Substance with a Union workplace exposure limit
(3) Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
Cellulose nitrate CAS: 9004-70-0 EC: 682-719-5	% (w/w) >=75.01: Expl. 1.1 - H201 % (w/w) >=1: Desen. Expl. 2 - H207

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
butan-1-ol	LD50 oral	800 mg/kg	Rat
CAS: 71-36-3	LD50 dermal	Not relevant	
EC: 200-751-6	LC50 inhalation	Not relevant	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

- CONTINUED ON NEXT PAGE -



SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

In case of fire follow the instructions on the Internal Emergency Plan

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

- CONTINUED ON NEXT PAGE -



SECTION 7: HANDLING AND STORAGE (continued)

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Maximum Temp.: 30 ºC

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC,Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
acetone	IOELV (8h)	500 ppm	1210 mg/m³
CAS: 67-64-1 EC: 200-662-2	IOELV (STEL)		
Dimethyl ether	IOELV (8h)	1000 ppm	1920 mg/m³
CAS: 115-10-6 EC: 204-065-8	IOELV (STEL)		
N-butyl acetate	IOELV (8h)	50 ppm	241 mg/m³
CAS: 123-86-4 EC: 204-658-1	IOELV (STEL)	150 ppm	723 mg/m³
2-methoxy-1-methylethyl acetate (1)	IOELV (8h)	50 ppm	275 mg/m³
CAS: 108-65-6 EC: 203-603-9	IOELV (STEL)	100 ppm	550 mg/m³

(1) Skin

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
acetone	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 67-64-1	Dermal	Not relevant	Not relevant	186 mg/kg	Not relevant
EC: 200-662-2	Inhalation	Not relevant	2420 mg/m³	1210 mg/m³	Not relevant
Dimethyl ether	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 115-10-6	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 204-065-8	Inhalation	Not relevant	Not relevant	1894 mg/m³	Not relevant
N-butyl acetate	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 123-86-4	Dermal	11 mg/kg	Not relevant	11 mg/kg	Not relevant
EC: 204-658-1	Inhalation	600 mg/m³	600 mg/m³	300 mg/m³	300 mg/m³
2-methoxy-1-methylethyl acetate	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 108-65-6	Dermal	Not relevant	Not relevant	796 mg/kg	Not relevant
EC: 203-603-9	Inhalation	Not relevant	550 mg/m³	275 mg/m³	Not relevant
butan-1-ol	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 71-36-3	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 200-751-6	Inhalation	Not relevant	Not relevant	Not relevant	310 mg/m³
trizinc bis(orthophosphate)	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 7779-90-0	Dermal	Not relevant	Not relevant	83 mg/kg	Not relevant
EC: 231-944-3	Inhalation	Not relevant	Not relevant	5 mg/m³	Not relevant

DNEL (General population):

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
acetone	Oral	Not relevant	Not relevant	62 mg/kg	Not relevant
CAS: 67-64-1	Dermal	Not relevant	Not relevant	62 mg/kg	Not relevant
EC: 200-662-2	Inhalation	Not relevant	Not relevant	200 mg/m³	Not relevant
Dimethyl ether	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 115-10-6	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 204-065-8	Inhalation	Not relevant	Not relevant	471 mg/m³	Not relevant
N-butyl acetate	Oral	2 mg/kg	Not relevant	2 mg/kg	Not relevant
CAS: 123-86-4	Dermal	6 mg/kg	Not relevant	6 mg/kg	Not relevant
EC: 204-658-1	Inhalation	300 mg/m³	300 mg/m³	35,7 mg/m³	35,7 mg/m³
2-methoxy-1-methylethyl acetate	Oral	Not relevant	Not relevant	36 mg/kg	Not relevant
CAS: 108-65-6	Dermal	Not relevant	Not relevant	320 mg/kg	Not relevant
EC: 203-603-9	Inhalation	Not relevant	Not relevant	33 mg/m³	33 mg/m³
butan-1-ol	Oral	Not relevant	Not relevant	1,562 mg/kg	Not relevant
CAS: 71-36-3	Dermal	Not relevant	Not relevant	3,125 mg/kg	Not relevant
EC: 200-751-6	Inhalation	Not relevant	Not relevant	55,357 mg/m³	155 mg/m³
trizinc bis(orthophosphate)	Oral	Not relevant	Not relevant	0,83 mg/kg	Not relevant
CAS: 7779-90-0	Dermal	Not relevant	Not relevant	83 mg/kg	Not relevant
EC: 231-944-3	Inhalation	Not relevant	Not relevant	2,5 mg/m³	Not relevant

PNEC:

Identification				
acetone	STP	100 mg/L	Fresh water	10,6 mg/L
CAS: 67-64-1	Soil	29,5 mg/kg	Marine water	1,06 mg/L
EC: 200-662-2	Intermittent	21 mg/L	Sediment (Fresh water)	30,4 mg/kg
	Oral	Not relevant	Sediment (Marine water)	3,04 mg/kg
Dimethyl ether	STP	160 mg/L	Fresh water	0,155 mg/L
CAS: 115-10-6	Soil	0,045 mg/kg	Marine water	0,016 mg/L
EC: 204-065-8	Intermittent	1,549 mg/L	Sediment (Fresh water)	0,681 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,069 mg/kg
N-butyl acetate	STP	35,6 mg/L	Fresh water	0,18 mg/L
CAS: 123-86-4	Soil	0,09 mg/kg	Marine water	0,018 mg/L
EC: 204-658-1	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,098 mg/kg
2-methoxy-1-methylethyl acetate	STP	100 mg/L	Fresh water	0,635 mg/L
CAS: 108-65-6	Soil	0,29 mg/kg	Marine water	0,064 mg/L
EC: 203-603-9	Intermittent	6,35 mg/L	Sediment (Fresh water)	3,29 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,329 mg/kg
butan-1-ol	STP	2476 mg/L	Fresh water	0,082 mg/L
CAS: 71-36-3	Soil	0,017 mg/kg	Marine water	0,008 mg/L
EC: 200-751-6	Intermittent	2,25 mg/L	Sediment (Fresh water)	0,324 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0,032 mg/kg
trizinc bis(orthophosphate)	STP	0,1 mg/L	Fresh water	0,0206 mg/L
CAS: 7779-90-0	Soil	35,6 mg/kg	Marine water	0,0061 mg/L
EC: 231-944-3	Intermittent	Not relevant	Sediment (Fresh water)	117,8 mg/kg
	Oral	Not relevant	Sediment (Marine water)	56,5 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,…) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

- CONTINUED ON NEXT PAGE -

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases, vapours and particles	CE CAT III	EN 149:2001+A1:2009 EN 405:2002+A1:2010 EN ISO 136:1998	Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	CE CAT III	EN ISO 21420:2020	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield	CE CAT II	EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer´s instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CE CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer´s instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CE CAT III	EN ISO 13287:2020 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	95,5 % weight
V.O.C. density at 20 ºC:	Not relevant
Average carbon number:	3,8
Average molecular weight:	75,49 g/mol

- CONTINUED ON NEXT PAGE -



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 ºC:	Aerosol
Appearance:	Not available
Colour:	Grey
Odour:	Solvent
Odour threshold:	Not relevant *

Volatility:

Boiling point at atmospheric pressure:	Not relevant *
Vapour pressure at 20 ºC:	4000 Pa
Vapour pressure at 50 ºC:	Not relevant *
Evaporation rate at 20 ºC:	Not relevant *

Product description:

Density at 20 ºC:	Not relevant *
Relative density at 20 ºC:	0,8
Dynamic viscosity at 20 ºC:	Not relevant *
Kinematic viscosity at 20 ºC:	Not relevant *
Kinematic viscosity at 40 ºC:	Not relevant *
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 ºC:	Not relevant *
Partition coefficient n-octanol/water 20 ºC:	Not relevant *
Solubility in water at 20 ºC:	Not relevant *
Solubility properties:	Insoluble in water
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *
Recipient pressure:	Not relevant *

Flammability:

Flash Point:	Non-applicable
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	240 ºC (Propellant)
Lower flammability limit:	1,2 % Volume
Upper flammability limit:	26,2 % Volume

Particle characteristics:

Median equivalent diameter:	Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Other safety characteristics:

Surface tension at 20 ºC:	Not relevant *
Refraction index:	Not relevant *

VOC (EY) 86,7 % 0,2 %
VOC-EU% 710,7 g/l 86,67 %

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Precaution	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO_2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

- CONTINUED ON NEXT PAGE -



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
  IARC: Titanium dioxide (2B)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
acetone	LD50 oral	5800 mg/kg	Rat
CAS: 67-64-1	LD50 dermal	7426 mg/kg	Rabbit
EC: 200-662-2	LC50 inhalation	76 mg/L (4 h)	Rat
Dimethyl ether	LD50 oral	>2000 mg/kg	
CAS: 115-10-6	LD50 dermal	>2000 mg/kg	
EC: 204-065-8	LC50 inhalation	308,5 mg/L (4 h)	Rat
N-butyl acetate	LD50 oral	12789 mg/kg	Rat
CAS: 123-86-4	LD50 dermal	14112 mg/kg	Rabbit
EC: 204-658-1	LC50 inhalation	23,4 mg/L (4 h)	Rat
Propane	LD50 oral	>2000 mg/kg	
CAS: 74-98-6	LD50 dermal	>2000 mg/kg	
EC: 200-827-9	LC50 inhalation	>5 mg/L	
2-methoxy-1-methylethyl acetate	LD50 oral	8532 mg/kg	Rat
CAS: 108-65-6	LD50 dermal	5100 mg/kg	Rat
EC: 203-603-9	LC50 inhalation	30 mg/L (4 h)	Rat
butan-1-ol	LD50 oral	800 mg/kg (ATEi)	Rat
CAS: 71-36-3	LD50 dermal	3430 mg/kg	Rabbit
EC: 200-751-6	LC50 inhalation	24,66 mg/L (4 h)	Rat
trizinc bis(orthophosphate)	LD50 oral	>2000 mg/kg	
CAS: 7779-90-0	LD50 dermal	>2000 mg/kg	
EC: 231-944-3	LC50 inhalation	>5 mg/L	
Titanium dioxide	LD50 oral	10000 mg/kg	Rat
CAS: 13463-67-7	LD50 dermal	10000 mg/kg	Rabbit
EC: 236-675-5	LC50 inhalation	>5 mg/L	

- CONTINUED ON NEXT PAGE -



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acute toxicity		Genus
Butane (containing ≥ 0,1 % butadiene (203-450-8))	LD50 oral	>2000 mg/kg	
CAS: 106-97-8	LD50 dermal	>2000 mg/kg	
EC: 203-448-7	LC50 inhalation	658 mg/L (4 h)	Rat
Isobutane (containing ≥ 0,1 % butadiene (203-450-8))	LD50 oral	>2000 mg/kg	
CAS: 75-28-5	LD50 dermal	>2000 mg/kg	
EC: 200-857-2	LC50 inhalation	>5 mg/L	
Cellulose nitrate	LD50 oral	>2000 mg/kg	
CAS: 9004-70-0	LD50 dermal	>2000 mg/kg	
EC: 682-719-5	LC50 inhalation	>5 mg/L	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Harmful to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
acetone	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 67-64-1	EC50	8800 mg/L (48 h)	Daphnia pulex	Crustacean
EC: 200-662-2	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
N-butyl acetate	LC50	Not relevant		
CAS: 123-86-4	EC50	Not relevant		
EC: 204-658-1	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
2-methoxy-1-methylethyl acetate	LC50	161 mg/L (96 h)	Pimephales promelas	Fish
CAS: 108-65-6	EC50	481 mg/L (48 h)	Daphnia sp.	Crustacean
EC: 203-603-9	EC50	Not relevant		
butan-1-ol	LC50	1740 mg/L (96 h)	Pimephales promelas	Fish
CAS: 71-36-3	EC50	1983 mg/L (48 h)	Daphnia magna	Crustacean
EC: 200-751-6	EC50	500 mg/L (96 h)	Scenedesmus subspicatus	Algae
trizinc bis(orthophosphate)	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: 7779-90-0	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
EC: 231-944-3	EC50	>0.1 - 1 mg/L (72 h)		Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
acetone	NOEC	Not relevant		
CAS: 67-64-1 EC: 200-662-2	NOEC	2212 mg/L	Daphnia magna	Crustacean
N-butyl acetate	NOEC	Not relevant		
CAS: 123-86-4 EC: 204-658-1	NOEC	23,2 mg/L	Daphnia magna	Crustacean
2-methoxy-1-methylethyl acetate	NOEC	47,5 mg/L	Oryzias latipes	Fish
CAS: 108-65-6 EC: 203-603-9	NOEC	100 mg/L	Daphnia magna	Crustacean
butan-1-ol	NOEC	Not relevant		
CAS: 71-36-3 EC: 200-751-6	NOEC	4,1 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Degradability		Biodegradability	
acetone	BOD5	Not relevant	Concentration	100 mg/L
CAS: 67-64-1	COD	Not relevant	Period	28 days
EC: 200-662-2	BOD5/COD	Not relevant	% Biodegradable	96 %
N-butyl acetate	BOD5	Not relevant	Concentration	Not relevant
CAS: 123-86-4	COD	Not relevant	Period	5 days
EC: 204-658-1	BOD5/COD	Not relevant	% Biodegradable	84 %
2-methoxy-1-methylethyl acetate	BOD5	Not relevant	Concentration	785 mg/L
CAS: 108-65-6	COD	Not relevant	Period	8 days
EC: 203-603-9	BOD5/COD	Not relevant	% Biodegradable	100 %
butan-1-ol	BOD5	1,71 g O2/g	Concentration	Not relevant
CAS: 71-36-3	COD	2,46 g O2/g	Period	19 days
EC: 200-751-6	BOD5/COD	0,7	% Biodegradable	98 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
acetone	BCF	1
CAS: 67-64-1	Pow Log	-0.24
EC: 200-662-2	Potential	Low
N-butyl acetate	BCF	4
CAS: 123-86-4	Pow Log	1.78
EC: 204-658-1	Potential	Low
2-methoxy-1-methylethyl acetate	BCF	1
CAS: 108-65-6	Pow Log	0.43
EC: 203-603-9	Potential	Low
Propane	BCF	13
CAS: 74-98-6	Pow Log	2.86
EC: 200-827-9	Potential	Low
Butane (containing ≥ 0,1 % butadiene (203-450-8))	BCF	33
CAS: 106-97-8	Pow Log	2.89
EC: 203-448-7	Potential	Moderate
butan-1-ol	BCF	1
CAS: 71-36-3	Pow Log	0.88
EC: 200-751-6	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
acetone	Koc	1	Henry	2,93 Pa·m³/mol
CAS: 67-64-1	Conclusion	Very High	Dry soil	Yes
EC: 200-662-2	Surface tension	2,304E-2 N/m (25 ºC)	Moist soil	Yes
Dimethyl ether	Koc	Not relevant	Henry	Not relevant
CAS: 115-10-6	Conclusion	Not relevant	Dry soil	Not relevant
EC: 204-065-8	Surface tension	1,136E-2 N/m (25 ºC)	Moist soil	Not relevant
N-butyl acetate	Koc	Not relevant	Henry	Not relevant
CAS: 123-86-4	Conclusion	Not relevant	Dry soil	Not relevant
EC: 204-658-1	Surface tension	2,478E-2 N/m (25 ºC)	Moist soil	Not relevant
Propane	Koc	460	Henry	71636,78 Pa·m³/mol
CAS: 74-98-6	Conclusion	Moderate	Dry soil	Yes
EC: 200-827-9	Surface tension	7,02E-3 N/m (25 ºC)	Moist soil	Yes
Butane (containing ≥ 0,1 % butadiene (203-450-8))	Koc	Not relevant	Henry	Not relevant
CAS: 106-97-8	Conclusion	Not relevant	Dry soil	Not relevant
EC: 203-448-7	Surface tension	1,187E-2 N/m (25 ºC)	Moist soil	Not relevant

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volatility	
Isobutane (containing ≥ 0,1 % butadiene (203-450-8))	Koc	Not relevant	Henry	Not relevant
CAS: 75-28-5	Conclusion	Not relevant	Dry soil	Not relevant
EC: 200-857-2	Surface tension	9,84E-3 N/m (25 ºC)	Moist soil	Not relevant
butan-1-ol	Koc	2.44	Henry	5,39E-2 Pa·m³/mol
CAS: 71-36-3	Conclusion	Very High	Dry soil	Yes
EC: 200-751-6	Surface tension	2,567E-2 N/m (25 ºC)	Moist soil	Yes

Insoluble in water

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
15 01 04 08 01 11*	metallic packaging waste paint and varnish containing organic solvents or other hazardous substances	Hazardous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP7 Carcinogenic, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:

- CONTINUED ON NEXT PAGE -

SECTION 14: TRANSPORT INFORMATION (continued)



14.1	**UN number or ID number:**	UN1950
14.2	**UN proper shipping name:**	AEROSOLS
14.3	**Transport hazard class(es):**	2
	Labels:	2.1
14.4	**Packing group:**	N/A
14.5	**Environmental hazards:**	No
14.6	**Special precautions for user**	
	Special regulations:	190, 327, 344, 625
	Tunnel restriction code:	D
	Physico-Chemical properties:	see section 9
	Limited quantities:	1 L
14.7	**Maritime transport in bulk according to IMO instruments:**	Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 41-22:



14.1	**UN number or ID number:**	UN1950
14.2	**UN proper shipping name:**	AEROSOLS
14.3	**Transport hazard class(es):**	2
	Labels:	2.1
14.4	**Packing group:**	N/A
14.5	**Marine pollutant:**	No
14.6	**Special precautions for user**	
	Special regulations:	63, 959, 190, 277, 327, 344
	EmS Codes:	F-D, S-U
	Physico-Chemical properties:	see section 9
	Limited quantities:	1 L
	Segregation group:	Not relevant
14.7	**Maritime transport in bulk according to IMO instruments:**	Not relevant

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:



14.1	**UN number or ID number:**	UN1950
14.2	**UN proper shipping name:**	AEROSOLS
14.3	**Transport hazard class(es):**	2
	Labels:	2.1
14.4	**Packing group:**	N/A
14.5	**Environmental hazards:**	No
14.6	**Special precautions for user**	
	Physico-Chemical properties:	see section 9
14.7	**Maritime transport in bulk according to IMO instruments:**	Not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

- CONTINUED ON NEXT PAGE -



SECTION 15: REGULATORY INFORMATION (continued)

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a	FLAMMABLE AEROSOLS	150	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9. However, products that contain explosives precursors only to such a small extent and in such complex mixtures that the extraction of the explosives precursors is technically extremely difficult should be excluded from the scope of this Regulation.
Shall not be used in:
—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
—tricks and jokes,
—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):
· Precautionary statements

Texts of the legislative phrases mentioned in section 2:

H222: Extremely flammable aerosol.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
H412: Harmful to aquatic life with long lasting effects.
H229: Pressurised container: May burst if heated.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed.
Aquatic Acute 1: H400 - Very toxic to aquatic life.
Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
Carc. 2: H351 - Suspected of causing cancer.
Expl. 1.1: H201 - Explosive, mass explosion hazard.
Eye Dam. 1: H318 - Causes serious eye damage.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Gas 1A: H220 - Extremely flammable gas.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Press. Gas (Liq.): H280 - Contains gas under pressure, may explode if heated.
Press. Gas: H280 - Contains gas under pressure, may explode if heated.
Skin Irrit. 2: H315 - Causes skin irritation.
STOT SE 3: H335 - May cause respiratory irritation.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Advice related to training:

- CONTINUED ON NEXT PAGE -



SECTION 16: OTHER INFORMATION (continued)

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu
http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -