MAX(° GFAD

Safety data sheet

This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

MAXX GEAR Metal Putty



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: MAXX GEAR Metal Putty

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Fillers

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Rakennuskemia Oy Kerkkolankatu 17

05800 Hyvinkää - Finland Phone.: +358 19 4574400 info@rakennuskemia.com www.rakennuskemia.com

1.4 Emergency telephone number:

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Liq. 3: Flammable liquids, Category 3, H226 Repr. 2: Reproductive toxicity, Category 2, H361d Skin Irrit. 2: Skin irritation, Category 2, H315

STOT RE 2: Specific target organ toxicity by inhalation, repeated exposure, Category 2, H373

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Warning







Hazard statements:

Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 3: H226 - Flammable liquid and vapour

Repr. 2: H361d - Suspected of damaging the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation)

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand

P102: Keep out of reach of children

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P260: Do not breathe vapours

P280: Wear protective gloves/eye protection

P281: Use personal protective equipment as required

P314: Get medical advice/attention if you feel unwell

P405: Store locked up

P501: Dispose of contents/container according to the separated collection system used in your municipality

UFI: F7DY-285K-Y30M-CH8C

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/12/2020 Revised: 21/12/2020 Version: 2 (Replaced 1) Page 1/12

MAX(° GEAR

Safety data sheet

This SDS is an English translation of Regulation (EU) $n^{\rm o}$ 2015/830, without any country-specific legislation

MAXX GEAR Metal Putty







SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Non-applicable

3.2 Mixture:

Chemical description: Filler

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| | Identification | tion Chemical name/Classification C | | | | |
|-------------------------|--|-------------------------------------|---|--------------------------|-----------|--|
| CAS: | 7727-43-7 | Barium Sulfate(1) | | Not classified | | |
| EC: Index: REACH: | 231-784-4 Non-applicable : 01-2119491274-35- XXXX | Regulation 1272/2008 | | | 5 - <10 % | |
| CAS: | 100-42-5 202-851-5 601-026-00-0 : 01-2119457861-32- XXXX | styrene ⁽¹⁾ ATP ATP06 | | | | |
| EC: Index: REACH: | | Regulation 1272/2008 | Acute Tox. 4: H332; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 1: H372 - Danger | (1) (b) (\$\dag{\lambda} | 5 - <10 % | |
| CAS: | 25013-15-4 | Vinyltoluene(1) | | Self-classified | | |
| EC: Index: REACH: | 246-562-2 Non-applicable 01-2119622074-50- XXXX | Regulation 1272/2008 | Aquatic Chronic 2: H411; Flam. Liq. 3: H226 - Warning | (1) | <2,5 % | |

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/12/2020 Revised: 21/12/2020 Version: 2 (Replaced 1) Page 2/12

. This SDS is an English translation of Regulation (EU) $n^{\rm o}$ 2015/830, without any country-specific legislation

MAXX GEAR Metal Putty







SECTION 5: FIREFIGHTING MEASURES (continued)

5.1 **Extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

Environmental precautions: 6.2

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

- CONTINUED ON NEXT PAGE -

Revised: 21/12/2020 Date of compilation: 10/12/2020 Version: 2 (Replaced 1) Page 3/12

This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

MAXX GEAR Metal Putty





SECTION 7: HANDLING AND STORAGE (continued)

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

Conditions for safe storage, including any incompatibilities: 7.2

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

Specific end use(s): 7.3

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 **Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

| Identification | Осси | Occupational exposure limits | | |
|------------------------------|--------------|------------------------------|--|--|
| Barium Sulfate | IOELV (8h) | 0.5 mg/m ³ | | |
| CAS: 7727-43-7 EC: 231-784-4 | IOELV (STEL) | | | |

DNEL (Workers):

| | | Short exposure | | Long exposure | |
|----------------|------------|-----------------------|-----------------------|----------------------|----------------------|
| Identification | | Systemic | Local | Systemic | Local |
| Barium Sulfate | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 7727-43-7 | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| EC: 231-784-4 | Inhalation | Non-applicable | Non-applicable | 10 mg/m ³ | 10 mg/m ³ |
| styrene | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 100-42-5 | Dermal | Non-applicable | Non-applicable | 406 mg/kg | Non-applicable |
| EC: 202-851-5 | Inhalation | 289 mg/m ³ | 306 mg/m ³ | 85 mg/m ³ | Non-applicable |

DNEL (General population):

| | | Short e | xposure | Long e | xposure |
|----------------|------------|--------------------------|--------------------------|------------------------|----------------|
| Identification | | Systemic | Local | Systemic | Local |
| Barium Sulfate | Oral | Non-applicable | Non-applicable | 13000 mg/kg | Non-applicable |
| CAS: 7727-43-7 | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| EC: 231-784-4 | Inhalation | Non-applicable | Non-applicable | 10 mg/m ³ | Non-applicable |
| styrene | Oral | Non-applicable | Non-applicable | 2,1 mg/kg | Non-applicable |
| CAS: 100-42-5 | Dermal | Non-applicable | Non-applicable | 343 mg/kg | Non-applicable |
| EC: 202-851-5 | Inhalation | 174,25 mg/m ³ | 182,75 mg/m ³ | 10,2 mg/m ³ | Non-applicable |

PNEC:

| Identification | | | | |
|----------------|--------------|----------------|-------------------------|----------------|
| Barium Sulfate | STP | 62,2 mg/L | Fresh water | 0,115 mg/L |
| CAS: 7727-43-7 | Soil | 207,7 mg/kg | Marine water | Non-applicable |
| EC: 231-784-4 | Intermittent | Non-applicable | Sediment (Fresh water) | 600,4 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | Non-applicable |

Date of compilation: 10/12/2020 Revised: 21/12/2020 Version: 2 (Replaced 1) Page 4/12



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

MAXX GEAR Metal Putty







SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Identification | | | | |
|----------------|--------------|----------------|-------------------------|-------------|
| styrene | STP | 5 mg/L | Fresh water | 0,028 mg/L |
| CAS: 100-42-5 | Soil | 0,2 mg/kg | Marine water | 0,014 mg/L |
| EC: 202-851-5 | Intermittent | 0,04 mg/L | Sediment (Fresh water) | 0,614 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,307 mg/kg |

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|-----------------------------------|-----------|---------------------|--|
| Mandatory respiratory tract protection | Filter mask for gases and vapours | CAT III | EN 405:2001+A1:2009 | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |

C.- Specific protection for the hands

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---------------------------|---|-----------|---|--|
| Mandatory hand protection | NON-disposable chemical protective gloves | CAT III | EN ISO 374-1:2016 EN 16523-1:2015 EN 420:2003+A1:2009 | The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. |

[&]quot;As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

D.- Ocular and facial protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---------------------------|-------------|-----------|---|---|
| Mandatory face protection | Face shield | CATII | EN 166:2001 EN 167:2001 EN 168:2001 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|------------------------------------|--|-----------|---|---|
| Mandatory complete body protection | Disposable clothing for protection against chemical risks, with antistatic and fireproof properties | CAT III | EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982- 1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994 | For professional use only. Clean periodically according to the manufacturer's instructions. |
| Mandatory foot protection | Safety footwear for protection against chemical risk, with antistatic and heat resistant properties | CAT III | EN ISO 13287:2012 EN ISO 20345:2011 EN 13832-1:2019 | Replace boots at any sign of deterioration. |

F.- Additional emergency measures

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/12/2020 Revised: 21/12/2020 Version: 2 (Replaced 1) Page 5/12



Safety data sheet

This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

MAXX GEAR Metal Putty







SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Emergency measure | Emergency measure Standards | | Standards | |
|-------------------|---|------------------|--|--|
| Emergency shower | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 | Eyewash stations | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 | |

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

12,5 % weight V.O.C. (Supply):

136,88 kg/m³ (136,88 g/L) V.O.C. density at 20 °C:

Average carbon number: 8,2 Average molecular weight: 107 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid Fluid Appearance:

Colour: According to the markings on the package

Odour: Characteristic Odour threshold: Non-applicable *

Volatility:

Boiling point at atmospheric pressure: 145 °C Vapour pressure at 20 °C: 2301 Pa

Vapour pressure at 50 °C: 12126,83 Pa (12,13 kPa)

Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: 1095 kg/m³ Relative density at 20 °C: 1,095 Dynamic viscosity at 20 °C: 1,29 cP Kinematic viscosity at 20 °C: 1,18 cSt

Non-applicable * Kinematic viscosity at 40 °C: Concentration: Non-applicable * Non-applicable * pH: Vapour density at 20 °C: Non-applicable * Partition coefficient n-octanol/water 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility properties: Non-applicable * Decomposition temperature: Non-applicable * Melting point/freezing point: Non-applicable * Explosive properties: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/12/2020 Revised: 21/12/2020 Version: 2 (Replaced 1) Page 6/12



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

MAXX GEAR Metal Putty







SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Oxidising properties: Non-applicable *

Flammability:

Flash Point: 31 °C

Flammability (solid, gas): Non-applicable *

480 °C Autoignition temperature: Lower flammability limit: Not available Not available Upper flammability limit:

Explosive:

Non-applicable * Lower explosive limit: Upper explosive limit: Non-applicable *

9.2 Other information:

> Surface tension at 20 °C: Non-applicable * Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| 1 | Charle and Edition | Combant with air | T | Clih.b | University of the second |
|---|--------------------|------------------|-------------------------|---------------------|--------------------------|
| | Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
| | Not applicable | Not applicable | Risk of combustion | Avoid direct impact | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

- CONTINUED ON NEXT PAGE -

Revised: 21/12/2020 Date of compilation: 10/12/2020 Version: 2 (Replaced 1) Page 7/12

MAX(° GFAD

Safety data sheet

This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

MAXX GEAR Metal Putty



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

IARC: Vinyltoluene (3); styrene (2A)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Suspected of damaging the unborn child.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

| Identification | A | Genus | | |
|-----------------|---|-----------------|----------------|-----|
| Barium Sulfate | | LD50 oral | 15000 mg/kg | Rat |
| CAS: 7727-43-7 | | LD50 dermal | >2000 mg/kg | |
| EC: 231-784-4 | | LC50 inhalation | >5 mg/L (4 h) | |
| Vinyltoluene | | LD50 oral | 5100 mg/kg | Rat |
| CAS: 25013-15-4 | | LD50 dermal | >2000 mg/kg | |
| EC: 246-562-2 | | LC50 inhalation | >20 mg/L (4 h) | |
| styrene | | LD50 oral | >2000 mg/kg | |
| CAS: 100-42-5 | | LD50 dermal | >2000 mg/kg | |
| EC: 202-851-5 | | LC50 inhalation | 12 mg/L (4 h) | Rat |

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

MAXX GEAR Metal Putty







SECTION 12: ECOLOGICAL INFORMATION (continued)

| Identification | | Acute toxicity | Species | Genus |
|-----------------|------|-------------------|---------------------------|------------|
| Barium Sulfate | LC50 | 76000 mg/L (96 h) | Salmo gairdneri | Fish |
| CAS: 7727-43-7 | EC50 | Non-applicable | | |
| EC: 231-784-4 | EC50 | Non-applicable | | |
| Vinyltoluene | LC50 | 7.6 mg/L (96 h) | Salmo gairdneri | Fish |
| CAS: 25013-15-4 | EC50 | 1.3 mg/L (48 h) | Daphnia magna | Crustacean |
| EC: 246-562-2 | EC50 | 2.6 mg/L (72 h) | Selenastrum capricornutum | Algae |

12.2 Persistence and degradability:

Not available

12.3 Bioaccumulative potential:

| Identification | Bioaccumulation potential | | |
|-----------------|---------------------------|------|--|
| Vinyltoluene | BCF | 5 | |
| CAS: 25013-15-4 | Pow Log | 3.44 | |
| EC: 246-562-2 | Potential | Low | |

12.4 Mobility in soil:

| Identification | Absorpti | on/desorption | Volatility | | |
|-----------------|-----------------|---------------------|------------|----------------|--|
| styrene | Koc | Non-applicable | Henry | Non-applicable | |
| CAS: 100-42-5 | Conclusion | Non-applicable | Dry soil | Non-applicable | |
| EC: 202-851-5 | Surface tension | 3,21E-2 N/m (25 °C) | Moist soil | Non-applicable | |
| Vinyltoluene | Koc | Non-applicable | Henry | Non-applicable | |
| CAS: 25013-15-4 | Conclusion | Non-applicable | Dry soil | Non-applicable | |
| EC: 246-562-2 | Surface tension | 3,2E-2 N/m (20 °C) | Moist soil | Non-applicable | |

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|------|---|---|
| | It is not possible to assign a specific code, as it depends on the intended use by the user | Dangerous |

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP10 Toxic for reproduction, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION **

Transport of dangerous goods by land:

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/12/2020 Revised: 21/12/2020 Version: 2 (Replaced 1) Page 9/12

^{**} Changes with regards to the previous version

This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

MAXX GEAR Metal Putty







With regard to ADR 2019 and RID 2019:

14.1 UN number: UN3269

POLYESTER RESIN KIT, liquid base material 14.2 UN proper shipping name:

14.3 Transport hazard class(es): Labels: 3 14.4 Packing group: III

14.5 Environmental hazards: No

14.6 Special precautions for user

Special regulations: 236, 340 Tunnel restriction code:

see section 9 Physico-Chemical properties:

Limited quantities: 5 I

14.7 Transport in bulk according to Annex II of Marpol and

the IBC Code:

Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 39-18:

14.1 UN number: UN3269

14.2 UN proper shipping name: POLYESTER RESIN KIT, liquid base material

14.3 Transport hazard class(es): 3 Labels: 3

14.4 Packing group: TTT 14.5 Environmental hazards: No

14.6 Special precautions for user

Special regulations: 236, 340 EmS Codes: F-E, S-D Physico-Chemical properties: see section 9

Limited quantities: 5 L

Non-applicable Segregation group: 14.7 Transport in bulk according Non-applicable

to Annex II of Marpol and

the IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2020:

14.1 UN number:

14.2 UN proper shipping name: POLYESTER RESIN KIT, liquid base material

14.3 Transport hazard class(es): 3 Labels: III 14.4 Packing group:

14.5 Environmental hazards: Nο

14.6 Special precautions for user

Physico-Chemical properties: see section 9 14.7 Transport in bulk according Non-applicable

to Annex II of Marpol and

the IBC Code:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/12/2020 Revised: 21/12/2020 Version: 2 (Replaced 1) Page 10/12

^{**} Changes with regards to the previous version

MAX(° GEAR

Safety data sheet

This SDS is an English translation of Regulation (EU) $n^{\rm o}$ 2015/830, without any country-specific legislation

MAXX GEAR Metal Putty







SECTION 15: REGULATORY INFORMATION (continued)

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

| Section | Description | Lower-tier requirements | Upper-tier requirements |
|---------|-------------------|-------------------------|-------------------------|
| P5c | FLAMMABLE LIQUIDS | 5000 | 50000 |

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

TRANSPORT INFORMATION (SECTION 14):

- · UN number
- · Packing group

Texts of the legislative phrases mentioned in section 2:

H226: Flammable liquid and vapour

H315: Causes skin irritation

H319: Causes serious eye irritation

H361d: Suspected of damaging the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure (Inhalation)

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H332 - Harmful if inhaled

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects

Eye Irrit. 2: H319 - Causes serious eye irritation Flam. Liq. 3: H226 - Flammable liquid and vapour

Repr. 2: H361d - Suspected of damaging the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/12/2020 Revised: 21/12/2020 Version: 2 (Replaced 1) Page 11/12

MAX(° GEAR

Safety data sheet

This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

MAXX GEAR Metal Putty







SECTION 16: OTHER INFORMATION (continued)

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET
Date of compilation: 10/12/2020 Revised: 21/12/2020 Version: 2 (Replaced 1) Page 12/12

MAX(° GEAR

Safety data sheet

This SDS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation

MAXX GEAR Hardener Paste







SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: MAXX GEAR Hardener Paste

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Fillers

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Rakennuskemia Oy Kerkkolankatu 17 05800 Hyvinkää - Finland Phone : +358 10 4574400

Phone.: +358 19 4574400 info@rakennuskemia.com www.rakennuskemia.com

1.4 Emergency telephone number:

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 1: Hazardous to the aquatic environment, long-term hazard, Category 1, H410

Eye Irrit. 2: Eye irritation, Category 2, H319

Org. Perox. D: Organic peroxides, Category D, H242 Skin Sens. 1: Sensitisation, skin, Category 1, H317

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger







Hazard statements:

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects

Eye Irrit. 2: H319 - Causes serious eye irritation Org. Perox. D: H242 - Heating may cause a fire Skin Sens. 1: H317 - May cause an allergic skin reaction

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand

P102: Keep out of reach of children

P280: Wear protective gloves/eye protection

P302+P352: IF ON SKIN: Wash with plenty of water

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing

P403+P235: Store in a well-ventilated place. Keep cool

P501: Dispose of contents/container according to the separated collection system used in your municipality

Supplementary information:

Contains Dibenzoyl peroxide

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/12/2020 Revised: 21/12/2020 Version: 3 (Replaced 2) Page 1/12



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

MAXX GEAR Hardener Paste



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

3.2 Mixture:

Chemical description: Filler

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| | Identification | | Chemical name/Classification | | Concentration | | |
|--|--|---------------------------|--|-----------------|---------------|--|--|
| CAS: | 94-36-0 | Dibenzoyl peroxide (| Dibenzoyl peroxide (1) Self-classified | | | | |
| | 202-327-6 617-008-00-0 01-2119511472-50- XXXX | Regulation 1272/2008 | Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Irrit. 2: H319; Org. Perox. B: H241; Skin Sens. 1: H317 - Danger | | 25 - <50 % | | |
| CAS: | 131-11-3 | Dimethyl Phthalate(1 | .) | Not classified | | | |
| EC: 205-011-6 Index: Non-applicable REACH: 01-2119437229-36- XXXX | | Regulation 1272/2008 | | | 25 - <50 % | | |
| CAS: | 107-21-1 | Ethanediol ⁽¹⁾ | | Self-classified | | | |
| EC: Index: REACH: | 203-473-3 603-027-00-1 01-2119456816-28- XXXX | Regulation 1272/2008 | Acute Tox. 4: H302; STOT RE 2: H373 - Warning | <u>(1)</u> | 5 - <10 % | | |
| CAS: | 67762-90-7 | Siloxanes and Silicor | nes, di-Me, reaction products with silica(1) | Not classified | | | |
| EC: Index: REACH: | Non-applicable Non-applicable Non-applicable | Regulation 1272/2008 | | | 5 - <10 % | | |

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product does not contain substances classified as hazardous for inhalation, however, in case of symptoms of intoxication remove the person affected from the exposure area and provide with fresh air. Seek medical attention if the symptoms get worse or persist.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/12/2020 Revised: 21/12/2020 Version: 3 (Replaced 2) Page 2/12

. This SDS is an English translation of Regulation (EU) $n^{\rm o}$ 2015/830, without any country-specific legislation

MAXX GEAR Hardener Paste







SECTION 5: FIREFIGHTING MEASURES (continued)

5.1 **Extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO₂). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: 6.1

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

Environmental precautions: 6.2

Avoid at all cost any type of spillage into an agueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/12/2020 Revised: 21/12/2020 Version: 3 (Replaced 2) Page 3/12

Safety data sheet

This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation









SECTION 7: HANDLING AND STORAGE (continued)

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 **Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

| Identification | Occupational exposure limits | | | |
|-----------------------------|------------------------------|--------|-----------------------|--|
| Ethanediol | IOELV (8h) | 20 ppm | 52 mg/m ³ | |
| CAS: 107-21-1 EC: 203-473-3 | IOELV (STEL) | 40 ppm | 104 mg/m ³ | |

DNEL (Workers):

| | | Short exposure | | Long exposure | |
|--------------------|------------|----------------|----------------|------------------------|----------------------|
| Identification | | Systemic | Local | Systemic | Local |
| Dibenzoyl peroxide | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 94-36-0 | Dermal | Non-applicable | Non-applicable | 13,3 mg/kg | Non-applicable |
| EC: 202-327-6 | Inhalation | Non-applicable | Non-applicable | 39 mg/m ³ | Non-applicable |
| Dimethyl Phthalate | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 131-11-3 | Dermal | Non-applicable | Non-applicable | 135 mg/kg | Non-applicable |
| EC: 205-011-6 | Inhalation | Non-applicable | Non-applicable | 66,1 mg/m ³ | Non-applicable |
| Ethanediol | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 107-21-1 | Dermal | Non-applicable | Non-applicable | 106 mg/kg | Non-applicable |
| EC: 203-473-3 | Inhalation | Non-applicable | Non-applicable | Non-applicable | 35 mg/m ³ |

DNEL (General population):

| | | Short exposure | | Long exposure | |
|--------------------|------------|----------------|----------------|------------------------|----------------|
| Identification | | Systemic | Local | Systemic | Local |
| Dibenzoyl peroxide | Oral | Non-applicable | Non-applicable | 2 mg/kg | Non-applicable |
| CAS: 94-36-0 | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| EC: 202-327-6 | Inhalation | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| Dimethyl Phthalate | Oral | Non-applicable | Non-applicable | 9,4 mg/kg | Non-applicable |
| CAS: 131-11-3 | Dermal | Non-applicable | Non-applicable | 67,5 mg/kg | Non-applicable |
| EC: 205-011-6 | Inhalation | Non-applicable | Non-applicable | 16,3 mg/m ³ | Non-applicable |
| Ethanediol | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| CAS: 107-21-1 | Dermal | Non-applicable | Non-applicable | 53 mg/kg | Non-applicable |
| EC: 203-473-3 | Inhalation | Non-applicable | Non-applicable | Non-applicable | 7 mg/m³ |

PNEC:

| Identification | | | | |
|--------------------|--------------|----------------|-------------------------|---------------|
| Dibenzoyl peroxide | STP | 0,35 mg/L | Fresh water | 0,00002 mg/L |
| CAS: 94-36-0 | Soil | 0,003 mg/kg | Marine water | 0,000002 mg/L |
| EC: 202-327-6 | Intermittent | 0,000602 mg/L | Sediment (Fresh water) | 0,013 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,001 mg/kg |
| Dimethyl Phthalate | STP | 4 mg/L | Fresh water | 0,192 mg/L |
| CAS: 131-11-3 | Soil | 3,16 mg/kg | Marine water | 0,019 mg/L |
| EC: 205-011-6 | Intermittent | 0,39 mg/L | Sediment (Fresh water) | 1,3 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 0,13 mg/kg |

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/12/2020 Revised: 21/12/2020 Version: 3 (Replaced 2) Page 4/12



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation









SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Identification | | | | |
|----------------|--------------|----------------|-------------------------|-----------|
| Ethanediol | STP | 199,5 mg/L | Fresh water | 10 mg/L |
| CAS: 107-21-1 | Soil | 1,53 mg/kg | Marine water | 1 mg/L |
| EC: 203-473-3 | Intermittent | 10 mg/L | Sediment (Fresh water) | 37 mg/kg |
| | Oral | Non-applicable | Sediment (Marine water) | 3,7 mg/kg |

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|-----------------------------------|-----------|---------------------|--|
| Mandatory respiratory tract protection | Filter mask for gases and vapours | CAT III | EN 405:2001+A1:2009 | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |

C.- Specific protection for the hands

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---------------------------|--|-----------|--------------|--|
| Mandatory hand protection | Protective gloves against minor risks | CATI | | Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2003+A1:2009 and EN ISO 374-1:2016 |

[&]quot;As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

D.- Ocular and facial protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---------------------------|--|-----------|---------------------------------|---|
| Mandatory face protection | Panoramic glasses against splash/projections. | CATII | EN 166:2001 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|------------------------------------|---|-----------|--|---|
| Mandatory complete body protection | Antistatic and fireproof protective clothing | CAT III | EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2001 EN ISO 14116:2015 EN 1149-5:2018 | Limited protection against flames. |
| Mandatory foot protection | Safety footwear with antistatic and heat resistant properties | CAT III | EN ISO 13287:2012 EN ISO 20345:2011 | Replace boots at any sign of deterioration. |

F.- Additional emergency measures

| Emergency measure | Standards | Emergency measure | Standards |
|-------------------|---|-------------------|--|
| Emergency shower | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 | Eyewash stations | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |

Date of compilation: 10/12/2020 Revised: 21/12/2020 Version: 3 (Replaced 2) Page 5/12

Safety data sheet
This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific

MAXX GEAR Hardener Paste



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 0 % weight $0 \text{ kg/m}^3 (0 \text{ g/L})$ V.O.C. density at 20 °C: Average carbon number: Non-applicable Average molecular weight: Non-applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid Paste Appearance: Colour: Pink

Odour: Characteristic Odour threshold: Non-applicable *

Volatility:

197 °C Boiling point at atmospheric pressure: Vapour pressure at 20 °C: 1457 Pa

Vapour pressure at 50 °C: 7682,24 Pa (7,68 kPa) Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: 1171,6 kg/m³

Relative density at 20 °C: 1,172 Dynamic viscosity at 20 °C: 62,98 cP Kinematic viscosity at 20 °C: 53,75 cSt Kinematic viscosity at 40 °C: >20,5 cSt Concentration: Non-applicable * pH: Non-applicable * Vapour density at 20 °C: Non-applicable *

Partition coefficient n-octanol/water 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Non-applicable * Solubility properties: Decomposition temperature: Non-applicable * Melting point/freezing point: Non-applicable * Explosive properties: Non-applicable *

Oxidising properties: H242 Heating may cause a fire

Flammability:

Flash Point: 111 °C

Flammability (solid, gas): Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/12/2020 Revised: 21/12/2020 Version: 3 (Replaced 2) Page 6/12



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

MAXX GEAR Hardener Paste







SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Autoignition temperature: 410 °C

Lower flammability limit: Non-applicable * Upper flammability limit: Non-applicable *

Explosive:

Non-applicable * Lower explosive limit: Upper explosive limit: Non-applicable *

9.2 Other information:

> Surface tension at 20 °C: Non-applicable * Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable | Not applicable | Precaution | Avoid direct impact | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|---------------------|----------------|---------------------|-----------------------|--|
| Avoid direct impact | Not applicable | Avoid direct impact | Avoid direct impact | Avoid alkalines, heavy metals, reducing agents, peroxide accelerating agents |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- B- Inhalation (acute effect):

Revised: 21/12/2020 Date of compilation: 10/12/2020 Version: 3 (Replaced 2) Page 7/12

MAX(° GFAD

Safety data sheet

This SDS is an English translation of Regulation (EU) $^{\circ}$ 2015/830, without any country-specific legislation

MAXX GEAR Hardener Paste





SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for skin contact. For more information see section 3.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
 - IARC: Dibenzoyl peroxide (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
 - Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

| Identification | A | cute toxicity | Genus |
|---|-----------------|------------------|-------|
| Dibenzoyl peroxide | LD50 oral | 7710 mg/kg | Rat |
| CAS: 94-36-0 | LD50 dermal | >2000 mg/kg | |
| EC: 202-327-6 | LC50 inhalation | >5 mg/L (4 h) | |
| Dimethyl Phthalate | LD50 oral | >2000 mg/kg | |
| CAS: 131-11-3 | LD50 dermal | >2000 mg/kg | |
| EC: 205-011-6 | LC50 inhalation | >20 mg/L (4 h) | |
| Ethanediol | LD50 oral | 500 mg/kg (ATEi) | |
| CAS: 107-21-1 | LD50 dermal | >2000 mg/kg | |
| EC: 203-473-3 | LC50 inhalation | >20 mg/L (4 h) | |
| Siloxanes and Silicones, di-Me, reaction products with silica | LD50 oral | >2000 mg/kg | |
| CAS: 67762-90-7 | LD50 dermal | >2000 mg/kg | |
| EC: Non-applicable | LC50 inhalation | Non-applicable | |

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available



Safety data sheet

This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation legislation









SECTION 12: ECOLOGICAL INFORMATION (continued)

12.1 Toxicity:

| Identification | | Acute toxicity | Species | Genus |
|--------------------|------|--------------------|---------------------------------|------------|
| Dibenzoyl peroxide | LC50 | 0.0602 mg/L (96 h) | Oncorhynchus mykiss | Fish |
| CAS: 94-36-0 | EC50 | 0.11 mg/L (48 h) | Daphnia magna | Crustacean |
| EC: 202-327-6 | EC50 | 0.071 mg/L (72 h) | Pseudokirchneriella subcapitata | Algae |
| Dimethyl Phthalate | LC50 | 39 mg/L (96 h) | Pimephales promelas | Fish |
| CAS: 131-11-3 | EC50 | 150 mg/L (24 h) | Daphnia magna | Crustacean |
| EC: 205-011-6 | EC50 | 204 mg/L (72 h) | Scenedesmus subspicatus | Algae |
| Ethanediol | LC50 | 53000 mg/L (96 h) | Pimephales promelas | Fish |
| CAS: 107-21-1 | EC50 | 51000 mg/L (48 h) | Daphnia magna | Crustacean |
| EC: 203-473-3 | EC50 | 24000 mg/L (168 h) | Selenastrum capricornutum | Algae |

12.2 Persistence and degradability:

| Identification | Degradability | | Biodegradab | ility |
|--------------------|---------------|----------------|-----------------|----------------|
| Dibenzoyl peroxide | BOD5 | Non-applicable | Concentration | Non-applicable |
| CAS: 94-36-0 | COD | Non-applicable | Period | 10 days |
| EC: 202-327-6 | BOD5/COD | Non-applicable | % Biodegradable | 68 % |
| Dimethyl Phthalate | BOD5 | 1.12 g O2/g | Concentration | 100 mg/L |
| CAS: 131-11-3 | COD | 0.74 g O2/g | Period | 28 days |
| EC: 205-011-6 | BOD5/COD | 1.52 | % Biodegradable | 93 % |
| Ethanediol | BOD5 | 0.47 g O2/g | Concentration | 100 mg/L |
| CAS: 107-21-1 | COD | 1.29 g O2/g | Period | 14 days |
| EC: 203-473-3 | BOD5/COD | 0.36 | % Biodegradable | 90 % |

12.3 Bioaccumulative potential:

| Identification | Bioaccu | Bioaccumulation potential | | |
|--------------------|-----------|---------------------------|--|--|
| Dimethyl Phthalate | BCF | 57 | | |
| CAS: 131-11-3 | Pow Log | 1.6 | | |
| EC: 205-011-6 | Potential | Moderate | | |
| Ethanediol | BCF | 10 | | |
| CAS: 107-21-1 | Pow Log | -1.36 | | |
| EC: 203-473-3 | Potential | Low | | |

12.4 Mobility in soil:

| Identification | Absorption/desorption | | Volatility | |
|--------------------|-----------------------|----------------------|------------|--------------------|
| Dibenzoyl peroxide | Koc | 6309.57 | Henry | Non-applicable |
| CAS: 94-36-0 | Conclusion | Immobile | Dry soil | Non-applicable |
| EC: 202-327-6 | Surface tension | Non-applicable | Moist soil | Non-applicable |
| Dimethyl Phthalate | Koc | Non-applicable | Henry | Non-applicable |
| CAS: 131-11-3 | Conclusion | Non-applicable | Dry soil | Non-applicable |
| EC: 205-011-6 | Surface tension | 4,044E-2 N/m (25 °C) | Moist soil | Non-applicable |
| Ethanediol | Koc | 0 | Henry | 1,327E-1 Pa·m³/mol |
| CAS: 107-21-1 | Conclusion | Very High | Dry soil | No |
| EC: 203-473-3 | Surface tension | 4,989E-2 N/m (25 °C) | Moist soil | No |

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/12/2020 Revised: 21/12/2020 Version: 3 (Replaced 2) Page 9/12



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

MAXX GEAR Hardener Paste







SECTION 13: DISPOSAL CONSIDERATIONS (continued)

| Code | Description | Waste class (Regulation (EU) No 1357/2014) | |
|------|---|---|--|
| | It is not possible to assign a specific code, as it depends on the intended use by the user | Dangerous | |

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION **

Transport of dangerous goods by land:

With regard to ADR 2019 and RID 2019:



14.1 UN number: UN3108

14.2 UN proper shipping name: ORGANIC PEROXIDE TYPE E, SOLID (Dibenzoyl peroxide)

14.3 Transport hazard class(es): 5.2 Labels: 5.2

14.4 Packing group: N/A **14.5 Environmental hazards:** Yes

14.6 Special precautions for user

Special regulations: 122, 274
Tunnel restriction code: D

Physico-Chemical properties: see section 9 Limited quantities: 500 g

14.7 Transport in bulk according to Annex II of Marpol and

to Annex II of Marpol and the IBC Code:

ling Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 39-18:

14.1 UN number: UN3108

14.2 UN proper shipping name: ORGANIC PEROXIDE TYPE E, SOLID (Dibenzoyl peroxide)

 14.3
 Transport hazard class(es):
 5.2

 Labels:
 5.2

 14.4
 Packing group:
 N/A

14.4 Packing group: N/A **14.5 Environmental hazards:** Yes

14.6 Special precautions for user

Special regulations: 122, 274

EmS Codes: F-J, S-R

Physico-Chemical properties: see section 9

Limited quantities: 500 g

Segregation group: Non-applicable

14.7 Transport in bulk according Non-applicable to Annex II of Marpol and

the IBC Code:

Transport of dangerous goods by air:

** Changes with regards to the previous version

- CONTINUED ON NEXT PAGE -

Date of compilation: 10/12/2020 Revised: 21/12/2020 Version: 3 (Replaced 2) Page 10/12

. This SDS is an English translation of Regulation (EU) $n^{\rm o}$ 2015/830, without any country-specific legislation

MAXX GEAR Hardener Paste







SECTION 14: TRANSPORT INFORMATION ** (continued)

With regard to IATA/ICAO 2020:



UN3108 14.1 UN number:

ORGANIC PEROXIDE TYPE E, SOLID (Dibenzoyl peroxide) 14.2 UN proper shipping name:

14.3 Transport hazard class(es): Labels: 5.2

14.4 Packing group: N/A 14.5 Environmental hazards:

14.6 Special precautions for user

Physico-Chemical properties: see section 9 14.7 Transport in bulk according Non-applicable

to Annex II of Marpol and

the IBC Code:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

| Section | Description | Lower-tier requirements | Upper-tier requirements |
|---------|---|-------------------------|-------------------------|
| P6b | SELF-REACTIVE SUBSTANCES AND MIXTURES and ORGANIC PEROXIDES | 50 | 200 |
| E1 | ENVIRONMENTAL HAZARDS | 100 | 200 |

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

- CONTINUED ON NEXT PAGE -

Revised: 21/12/2020 Date of compilation: 10/12/2020 Version: 3 (Replaced 2) Page 11/12

^{*} Changes with regards to the previous version

MAX(° GEAR

Safety data sheet

This SDS is an English translation of Regulation (EU) $n^{\rm o}$ 2015/830, without any country-specific legislation

MAXX GEAR Hardener Paste



SECTION 16: OTHER INFORMATION (continued)

TRANSPORT INFORMATION (SECTION 14):

- · UN number
- · Packing group

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation

H317: May cause an allergic skin reaction

H410: Very toxic to aquatic life with long lasting effects

H242: Heating may cause a fire

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H302 - Harmful if swallowed Aquatic Acute 1: H400 - Very toxic to aquatic life

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects

Eye Irrit. 2: H319 - Causes serious eye irritation

Org. Perox. B: H241 - Heating may cause a fire or explosion Skin Sens. 1: H317 - May cause an allergic skin reaction

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.