# TIMPURI

# **PRIMER**

EN

1/2

Updated: 24.11.2023



PRIMER		
Product size	1 L, 3 L	
Description	Water-based, synthetic rubber latex. Primer for porous and non-absorbent surfaces for indoor and outdoor use. To be used before waterproofing coating.	
TECHNICAL DATA		
Spreading capacity (Non absorbent surface)	Approx. 10 m²/ L	
Spreading capacity (Porous surfaces)	Approx. 6 m²∕ L	
Working temperature	Minimum +10°C degrees	
Drying time	2 - 4 h depending on the conditions.	
Dust dry	4 h	
Overpaintable	10 h	
Tools	Felt spatula, brush, roller, paintbrush	
Cleaning	Wash tools with water immediately after use.	
Shelf life	At least 1 year.	
Storage	At least +6°C degrees. In the tightly closed original container. Protect from freezing.	

### **SPECIAL FEATURES**

The product has a sufficient composition. Withstands alkalinity. Priming prevents the waterproofing coating and filler from drying out too quickly and improves adhesion.

#### **APPLICATIONS**

Concrete and cement-based fillers, chipboards, plasterboard floors with old adhesive residues such as artificial resin, bitumen or sulphite glue. The primer forms a good adhesion base for fillers and substrates. Binds and prevents dusting.

Continues on the next page...







## **PRIMER**



Updated: 24.11.2023

### PRETREATMENT OF THE SURFACE

Dirt, grease, dust, cement glue and all loose matter are removed from the substrate. If necessary, mechanical grinding is done.

#### **PAINTING CONDITIONS**

The surface must be dry, the temperature must be at least  $+5^{\circ}$ C degrees and the relative humidity below 80 %.

### **USE**

Mix the Primer well before use. The primer is applied in a thin, even layer, e.g. with a felt spatula or a brush. The primer must be dry before treating the surface (2-4 hours depending on the conditions).

Surface	Thinning recommendation
Concrete and cement-based screed	1 part Primer - 4 parts water
Substrates that do not tolerate moisture, e.g. plaster and wooden substrates	not thinned
Board floors, e.g. chipboard, plasterboard	not thinned
Floors with old adhesive residue	not thinned

### **ENVIRONMENTAL PROTECTION AND WASTE DISPOSAL**

Liquid waste must be delivered to a local hazardous waste disposal plant. Empty and dried packaging for normal waste collection or local hazardous waste disposal plant.



