



TOTAL FILL+

Updated: 31.01.2023



TOTAL FILL+	
Product size	150 ml
Colour	White
Description	Product is a lightweight, ready-mixed filler intended for small repairs of common interior surfaces of walls and ceilings.
TECHNICAL DATA	
Thinner	Water
Grain size	Max 0,10 mm
Density	Approx. 550 kg/m ³
Solid content	Approx. 45 % w/w
Filling capacity	Up to 15 mm per layer. Recommended to apply in multiple coats to achieve thicker layers.
Drying time	Approx. 30 min per mm, longer for thicker layers. Drying time varies depending on surface, temperature, relative humidity and other factors.
Operating temperature	+10°C - +35°C degrees. Relative humidity should be over 20 % RF.
Cleaning of tools	Water
Shelf life	Max 12 months in unopened package.
Storage	Store tightly closed in a cool place, +5°C - +20°C degrees. PROTECT AGAINST FROST!

INSTRUCTIONS

RK Total Fill+ is easy to work with, does not shrink and is easy to sand. The product has good adhesion to gypsum board, cement and plaster.

Application by hand using a putty knife. Product can be painted immediately when dry with water borne or solvent borne paint. Eye and face protection should be used during sanding. Filled surfaces should be precoated before wallpapering.

Do not use on surfaces with frequent water contact.

EN



1 / 1

TECHNICAL DATASHEET

TDS