WOODCARE.GUIDE

MOULD & MAINTENANCE CLEANER

EN

TECHNICAL DATASHEET

TDS

Updated: 26.10.2022



MOULD & MAINTENANCE CLEANER	
Product size	2,5 L
Description	Dilutable cleaning agent for removing impurities from the surfaces of structures, for outdoor use.
Color	Transparent
TECHNICAL DATA	
Composition	Active ingredient: Alkylbenzyldimethylammonium chloride
Spreading capacity	1 liter of diluted cleaning agent is enough for approx. 12-25 m²
Unit weight	1,07 Kg / L
Thinner	Water
pH	7,5
Lowest operating temperature	0 °C but works best at a temperature of +20°C ... +25°C degrees.
Tools	Sprayer, brush, pressure washer
Tool cleaning	Water
Shelf-life	At least 24 months
Storage	Sealed packaging and protected from frost.

FEATURES

As a maintenance cleaner removes dirt, grease, soot, pollen, etc. Suitable for painted and unpainted wooden surfaces. The maintenance cleaner does not fade the painted surfaces, so there is no need to repaint after washing. As a mould cleaner cleans the walls and terraces from dirt, algae, moss and mould. The treatment does not remove or fade the paint surface.

Continues on the next page...

Updated: 26.10.2022

APPLICATIONS
Dilutable detergent for wooden surfaces, such as maintenance cleaning of walls, fences, terraces, etc. Mould cleaner is suitable for outdoor use on wood, concrete and stone surfaces.

INSTRUCTIONS

USAGE
INSTRUCTIONS FOR USE AS A MOULD CLEANER:
Plants and soil must be properly protected during work. Dilute the cleaning agent 1:10 L with water. For demanding cleaning, the cleaning agent can be used undiluted. The detergent is sprayed (e.g. with a garden sprayer) or brushed onto the surface from the bottom up so that all surfaces get wet. The substance is allowed to act for 2-3 minutes and the cleaning is enhanced by brushing away the impurities. Finally, rinse with plenty of water from top to bottom. For very dirty surfaces, the treatment is repeated. NOTE: The pressure washer must be used with caution - the pressure must not be too strong. Do not use the pressure washer if the surface material is weak, cracked or the surface has some other structural weakness or risk of damage. The wood should be allowed to dry well before it is treated.

INSTRUCTIONS FOR USE AS A MAINTENANCE CLEANER:
Plants and soil must be properly protected during work. Dilute the cleaner 1:12 (one liter to twelve liters of water). For demanding cleaning, the mixing ratio is 1:5 (one liter to five liters of water). The detergent is sprayed (e.g. garden sprayer) or brushed onto the target and care is taken to wet all surfaces. The substance is allowed to act for 2-3 minutes and the cleaning is enhanced by brushing away the impurities. Finally, rinse with plenty of water. For very dirty surfaces, the treatment is repeated. NOTE: The pressure washer must be used with caution - the pressure must not be too strong. Do not use the pressure washer if the surface material is weak, cracked or the surface has some other structural weakness or risk of damage. The wood should be allowed to dry well before it is treated.

SAFETY
See Safety Data Sheet.

ENVIRONMENTAL PROTECTION AND WASTE DISPOSAL
Plants and soil must be properly protected during work. Recyclable packaging. Empty and dried packaging for normal waste collection and otherwise local hazardous waste disposal plant.

RAKENNUSKEMIA
Kerkkolankatu 17
05800 HYVINKÄÄ
info@rakennuskemia.fi
www.rakennuskemia.fi
Puh. 019 - 457 4400