WOODCARE.GUIDE

GARDEN FURNITURE & DECK OIL

EN

1 / 2

TECHNICAL DATASHEET

TDS

Updated: 14.03.2024



GARDEN FURNITURE & DECK OIL	
Product size	0,75 L; 2,7 L
Description	Special care/treatment oil for outdoor use, garden furniture, terraces or other oil-treated wooden structures.
Color	Transparent, Grey, Brown
TECHNICAL DATA	
Spreading capacity	8-10 m² / L
Drying time	Approx. 24 hours (+23 °C / 50 % RH)
Lowest operating temperature	+5 °C degrees
Tools	Brush of cloth
Tool cleaning	White spirit, followed by soap water
Shelf-life	At least 36 months
Storage	Sealed packaging and protected from frost.

FEATURES

Garden furniture and deck oil is suitable for all types of wood, including hardwoods such as teak, mahogany, pine, beech and oak. The oil penetrates deep into the wood, providing lasting protection against drying, moisture, dirt, fungi and decay. Strengthens the color and structure of the wood.

APPLICATIONS

Suitable for outdoor use, garden furniture, terraces or other oil-treated wooden structures.

Continues on the next page...

RAKENNUSKEMIA

Kerkkolankatu 17
05800 HYVINKÄÄ

info@rakennuskemia.fi
www.rakennuskemia.fi

Puh. 019 - 457 4400

Updated: 14.03.2024

INSTRUCTIONS

USAGE

The treated surface must be clean, dry and solid. During the applying and drying of the oil, the temperature of the oil, air and surface must be above +8 °C degrees and the relative humidity below 80 %. Thinner: water.

Apply an even layer of oil with a brush or cloth. Absorbent surfaces should be treated several times until the surface is saturated. Wipe off excess oil after an hour. First clean the brush with white spirit and then with soap water.

SAFETY

WARNING: Danger of spontaneous combustion in rags and cotton waste. Rags must be disposed of properly, e.g. by immersing in water or burning. (See Safety data sheet).

ENVIRONMENTAL PROTECTION AND WASTE DISPOSAL

Plants and soil must be properly protected during work. Recyclable packaging. Empty and dried packaging for normal waste collection and otherwise local hazardous waste disposal plant.

RAKENNUSKEMIA
Kerkkolankatu 17
05800 HYVINKÄÄ
info@rakennuskemia.fi
www.rakennuskemia.fi
Puh. 019 - 457 4400