

WOODCARE.GUIDE

COLD-PRESSED LINSEED OIL

Updated: 25.07.2022



COLD-PRESSED LINSEED OIL

Product size	250 ML, 1 L, 5 L
Description	Linseed oil is 100 % vegetable oil for the care and treatment of all wood.
Color	Transparent, lighter-colored woods get a light yellow color.

TECHNICAL DATA

Composition	Yellowish oily liquid
Unit weight	0,93 kg / L
Drying time	1-3 days depending on the surface and weather conditions
Tools	Brush
Tool cleaning	White spirit
Shelf-life	At least a year.
Storage	Sealed packaging and protected from frost.

FEATURES

Linseed oil leaves a 100% natural surface, emphasizing the natural texture of the wood. Gives the surface a beautiful, long-lasting and durable surface that protects against dirt, moisture and drying. Lighter-colored woods get a light yellow color.

APPLICATIONS

Suitable for the care and treatment of all wood.

Continues on the next page...

EN



1 / 2

TECHNICAL DATASHEET

TDS

WOODCARE.GUIDE

COLD-PRESSED LINSEED OIL

Updated: 25.07.2022

INSTRUCTIONS

Apply a generous amount of oil with a cloth or brush. After an hour, wipe off the excess oil. New or dried wood requires several treatments. However, the oil must be allowed to harden for at least 24 hours between each application. Tools are cleaned with white spirit immediately after use.

ENVIRONMENTAL PROTECTION AND WASTE DISPOSAL

Plants and soil must be properly protected during work. Recyclable packaging. Empty and dried packaging for normal waste collection and otherwise local hazardous waste disposal plant.

EN



2 / 2

TECHNICAL DATASHEET

TDS