SPRAY PAINTS

EN

TECHNICAL DATASHEET

TDS

Updated: 14.07.2022



SPRAY PAINTS	
Package sizes	400ml
Description	Quick-drying acrylic paint for surfaces made of wood, metal, aluminum, glass, stone and various plastics.
TECHNICAL DATA	
Composition	Acrylic resin
Color	See section Color options
VOC-Content	Ca. 89 %
Solid content	Ca. 11 %
Spreading capacity	1 - 1,75 m² (Depending on the surface)
Dust dry	Approx. after 5 minutes*
Touch dry	Approx. after 10 minutes*
Hardened / repaintability	Approx. after 1 hour*
Heat durability	+110 °C degrees
Shelf-life	10 years. Sell-by date indicated on the package (exp.)
Storage	Protect from direct sunlight, frost and moisture.

(*Drying time depends on the surface, the ambient temperature, humidity and the thickness of the paint applied.)

Continues on the next page...

RAKENNUSKEMIA

Kerkkolankatu 17
05800 HYVINKÄÄ
FINLAND

info@rakennuskemia.com
www.rakennuskemia.com
+358 - 19 - 457 4400

MAXX GEAR®

SPRAY PAINTS

EN

TECHNICAL DATASHEET

TDS

Updated: 14.07.2022

COLOR OPTIONS		
Color	RAL code	Gloss grade
Champion yellow Gloss	RAL1021	Gloss
X-treme Orange Gloss	RAL2009	Gloss
Italy Red Gloss	RAL3020	Gloss
Ultra Blue Gloss	RAL5002	Gloss
Epic Green Gloss	RAL6018	Gloss
Carbon Grey	RAL7016	Gloss
Rally White	RAL9003	Gloss & Matt
Rally Black	RAL9005	Gloss & Matt

FEATURES

- Excellent coverage
- Durable color and permanent gloss
- Scratch and wear resistant
- Does not drain easily
- Resistant to chemicals and the effects of the weather
- Excellent adhesion to various surfaces

USAGE

SURFACE PREPARATION/PRIMING

Remove old paint and rust from the surface to be painted. Sand the surface, clean, dry and degrease. Protect the environment. Apply a compatible primer. Sand the primer with fine sandpaper (P600).

PAINTING

Before painting, the surface must be clean, dry and free of grease. The spray paint should be at room temperature. The operating temperature should be +15 to +25 °C degrees. Shake for 2 minutes and spray on the test piece. Spray distance 25-30 cm. Apply several thin layers, remember to shake the spray

Continues on the next page...

Updated: 14.07.2022

paint between layers as well. Dust dry after 5-10 minutes. Completely dry after 1 hour. After use, turn the spray can upside down and spray for several seconds.

VARNISHING

Lightly sand the surface with fine sandpaper (P600). Clean the surface. Apply several thin layers of matching varnish. Remember to always shake between layers.

SHELF-LIFE

Sell-by date indicated on the package (exp.)

RAKENNUSKEMIA

Kerkkolankatu 17
05800 HYVINKÄÄ
FINLAND

info@rakennuskemia.com
www.rakennuskemia.com
+358 - 19 - 457 4400