

Updated: 14.07.2022



LACQUER CLEAR

Package sizes	400ml
Description	Quick-drying clear acrylic lacquer for painted surfaces, as well as wood, aluminium, glass, stone and various plastic surfaces.

TECHNICAL DATA

Composition	Acrylic resin
Color	Colorless
Gloss level	Gloss 90 (At an angle of 60°) Matt 10 (At an angle of 60°)
VOC content	Approx. 91 %
Solids	Approx. 9 %
Spreading capacity	1–1,75 m ² (depending on the surface)
Dust dry	After about 5 minutes*
Touch dry	After about 10 minutes*
Cured/paintable	After about 1 hour*
Temperature resistance	110°C
Shelf-life	10 years

* Drying time depends on the surface, ambient temperature, humidity and the thickness of the lacquer applied.

FEATURES

- Suitable for acrylic and nitrocellulose paints
- Fast-drying
- Durable gloss level, UV-resistant, fade resistant
- Not easily scratched
- Shockproof
- Resists different weather conditions
- Excellent adhesion
- Prevents corrosion

Continues on the next page...

Updated: 14.07.2022

EN



2 / 2

TECHNICAL DATASHEET

USAGE

Lightly sand the surface with fine sandpaper (P600). Clean the surface. The spray can should be at room temperature. The operating temperature should be +15°C ... +25°C. Shake for 2 minutes and spray on the test piece. Spraying distance 25–30 cm. Apply several thin layers, be sure to shake the spray can even between layers. Dust dry after 5–10 minutes. Completely dry after 1 hour. After use, turn the can upside down and spray for several seconds.

TDS