WHEEL SPRAY PAINT

EN

1 / 1

TECHNICAL DATASHEET

TDS

Updated: 13.07.2022



WHEEL SPRAY PAINT	
Package sizes	400ml
Description	Fast-drying acrylic paint especially for decoration and respraying of steel and alloy wheels and dust caps. Also suitable for many other materials.
TECHNICAL DATA	
Composition	Acrylic resin
Colors	Aluminum – Gloss Silver – Gloss Gold – Gloss
Spreading capacity	1–1,75 m² (Depending on the surface)
Dust dry	After about 5 minutes*
Touch dry	After about 10 minutes*
Cured/paintable	After about 2 hours*
Temperature resistance	110°C
Shelf-life	10 years

* Drying time depends on the surface, ambient temperature, humidity and the thickness of the lacquer applied.

FEATURES

- Durable color and lasting gloss
- Dries quickly
- Scratch and wear-resistant
- Does not run easily
- Resists chemicals and effects of the weather
- Excellent adhesion to various surfaces

USAGE

Remove old paint and rust from the surface to be painted. Sand the surface, clean, dry and remove grease. Protect the environment. Apply primer. The spray paint should be at room temperature. The operating temperature should be +15°C ... +25°C. Shake for 2 minutes and spray on the test piece. Spraying distance 25–30 cm. Apply many thin coats, be sure to shake the spray paint between coats. Dust dry after 5–10 minutes. Cures in 2 hours. To get a very glossy surface, add a layer of clear acrylic lacquer on top. After use, turn the can upside down and spray for several seconds.

RAKENNUSKEMIA

Kerkkolankatu 17
05800 HYVINKÄÄ
FINLAND

info@rakennuskemia.com
www.rakennuskemia.com
+358 - 19 - 457 4400