RUST STOP

EN

1 / 1

TECHNICAL DATASHEET

TDS

Updated: 14.07.2022



RUST STOP	
Package sizes	400ml
Description	Quick-drying nitrocellulose primer for treated and untreated metal surfaces. Also suitable for many other surfaces (plastic, wood stone, etc.). Prevents corrosion and protects against rust for a long time. 5-in-1: Primer, anti-rust, paint, protection and final finish in one paint.
TECHNICAL DATA	
Composition	Nitrocellulose
Spreading capacity	1–1,75 m² (Depending on the surface)
Dust dry	After about 8 to 10 minutes*
Cured	1 hour*
Shelf-life	10 years

* Drying time depends on the surface, ambient temperature, humidity and the thickness of the lacquer applied.

FEATURES

- Protects against corrosion
- Excellent coverage and adhesion
- Shock and vibration resistant

USAGE

Can be overpainted with almost any topcoat. Remove loose paint residue and rust. Sand the surface, clean, dry and remove grease. Protect the environment. Shake for two minutes before use and spray on the test piece. Spraying distance 25-30 cm. Apply many thin layers, be sure to shake the can between layers. Processing temperature +15°C ... +25°C. Dust dry after 8-10 minutes. Can be sanded/repainted after 1 hour. After use, turn the can upside down and spray for several seconds.

RAKENNUSKEMIA

Kerkkolankatu 17
05800 HYVINKÄÄ
FINLAND

info@rakennuskemia.com
www.rakennuskemia.com
+358 - 19 - 457 4400