# MULTI SPRAY MX-500

EN

1 / 1

TECHNICAL DATASHEET

TDS

Updated: 14.07.2022




| MULTI SPRAY MX-500 | |
|---|---|
| Package sizes | 400ml |
| Description | Multi Spray cleans, protects and lubricates almost anything. |
| **TECHNICAL DATA** | |
| Composition | Synthetic oil mixture |
| Color | Translucent light brown |
| VOC content | Approx. 82 % |
| Relative density (20°C) | 0,80 g/ml |
| Pressure (20°C) | 3–4 bar |
| Temperature resistance | -50°C ... +200°C |
| Shelf-life | 10 years |

## FEATURES

- Versatile multi-purpose oil
- Displaces moisture and prevents rust formation
- Leaves a protective film
- Cleansing effect
- Penetrates very tight spaces

## USAGE

The aerosol should be at room temperature. The operating temperature should be +5°C ... +30°C. Shake before use. Apply oil to the surface to be treated. Optimal lubrication is obtained after evaporation of the solvent. Repeat if necessary. Compatible surfaces: rubber, plastic, metal, aluminum, zinc, copper and other hard surfaces. Trying compatibility is always recommended.

RAKENNUSKEMIA

Kerkkolankatu 17
05800 HYVINKÄÄ
FINLAND

info@rakennuskemia.com
www.rakennuskemia.com
+358 - 19 - 457 4400